## HAUTED STATES

	Budget Bureau	No. 42-R142
IFASE		

UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	NM - 33015	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas [v]	West Fork	
well well other	9. WELL NO.	
2. NAME OF OPERATOR	#1	
Southland Royalty Company	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Gallegos Gallup Ustoc Tff	
P.O. Drawer 570, Farmington, NM 87499	11. SEC., T., R., M., OR BLK. AND SÚRVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17		
below.) at surface: 940' FNL & 1560' FWL	Section 14, T 26N, R12W	
AT SURFACE: 940' FNL & 1560' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE	
AT TOTAL DEPTH:	San Juan New Mexico	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.	
REPORT, OR OTHER DATA	15 SUSVATIONS (OLIOW DE KOD AND MED)	
·	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF TEST WATER SHUT-OFF SHOOT OF ACIDIZE	American Company of the Company of t	
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING		
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone SURVE change on Form 9–330.)	
REPAIR WELL  PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone	
MULTIPLE COMPLETE	AL SURVEY	
CHANGE ZONES	o. M.	
ABANDON*		
(other) Spud & Surface Casing X		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stational including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined.)	directionally drilled, give subsurface locations and	
4-1-83 Spudded 12-1/4" surface hole on 4-1-83 at 230'. Set five joints (212') of 8-5/8", 2 with 177 cubic feet of Class "B" containing pm on 4-1-83. Cement circulated to surface	24#, casing at 226'. Cemented on 3% CaCL2. Plug down at 7:30	
	A CEIVE	
Subsurface Safety Valve: Manu. and Type	Set @ Ft. DIV.	
18. I hereby certify that the foregoing is true and correct	with the second	
7/ -1 - 7	4 17 0 7000	
SIGNED Shury THE Secretary	DATEApril 8, 1983	
(This space for Federal or State of		
APPROVED BY TITLE	DATE	
CONDITIONS OF APPROVAL, IF ANY:	LUCCIO LA CON DEGODO	

\*See Instructions on Reverse Side

APR 1 4 1983

ALCEPTEU FOR RECORD

FARMINGTON DISTRICT