	5 BLM 1 Southla	and Royalty 1	File / Hawthor	orm Approved.	
Form 9–331 Dec. 1973	3 BEIT 1 SOUCHTE	and hojurty .	011 B	udget Bureau No. 42-R1424	
Dec. 1973	UNITED STATES  DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY		5. LEASE	NM 57580	
			6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
	NOTIOES AND DEE	ODTS ON WELLS	7. UNIT AGREEMEN	T NAME	
SUNDR	RY NOTICES AND REF	senen or plug back to a difference	nt		
(Do not use thi reservoir, Use I	Form 9-331-C for such proposals.)			NAME	
1. oil —	gas (V)		Irish		
well L	well X other		9. WELL NO.		
2. NAME C	OF OPERATOR		10. FIEDOR WILDC	AT NAME	
	DUGAN PRODUCTION CORP.			WAW Pictured Cliffs	
3. ADDRESS OF OPERATOR P O Box 208, Farmington, NM 87499			11. SEC., T., R., M.,	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17			AREA	Sec. 11 T26N R13W, NMPM	
below.) AT SURFACE: 1850' FSL - 790' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:			12. COUNTY OR PAR		
			San Juan	NM	
			14. API NO.	<u> </u>	
		CATE NATURE OF NOTIC		· .	
REPORT	. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		15. ELEVATIONS (SI	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
	CIR	BSEQUENT REPORT OF:	6129' GL		
	OK MITKOWNE VE	T			
FRACTURE	R SHUT∙OFF ∐ TREAT □		14 E D		
SHOOT OR	ACIDIZE		***	of multiple completion or zone	
REPAIR WE	LL U  LTER CASING		change on For		
MULTIPLE (			2.3		
CHANGE ZO		HEALES AND AND			
ABANDON*		XX T.D. and 2	-7/8" OD Casing		
(other)				and give pertinent dates.	
	IBE PROPOSED OR COMPLETE			subsurface locations and	
messur	ng estimated date of starting all red and true vertical depths for	all markers and zones pert	inent to this work.)*		
_	D 10001	10 15 0/			
7	D. 1380' reached on I.H. and conditioned	hole laid down	drill pipe. Riga	ed up and ran 64 jts	
2-	7/8" OD, 6.4#, 10 Rd 380' GL. Cemented wi	N.E.U.E ERW to	bing for casing (	T.E. 1380.29') set a	
<u>-</u>	380' GL. Cemented wi	th 75 sks 2% loder	ise with ¼# cellof	lake per sk, followe	
h.	, 50 cks class "R" ne.	at with %# cellot!	ake ber sk. Keci	procated pipe on	
wh	nile cementing. Good	circulation throu	ighout job. Circu	lated trace of good	
CE	ement to surface. P.	0.B. at 2:30 PM 10	)-16-84.		
		Fig. 6	'AFIBBE		
		TAN E	WEIVEM		
		UU			
		0	GENVED CT22 1984		
Subsurface	Safety Valve: Manu. and Type		COM NO	Set @ Ft.	
10 11	y certify that the foregoing is tru	ie and correct	COIN. DIV.	. ·	
18. Thereb	Sylver (ITY that the loregoing is the	Coologi	DIST. 3	17-84	
SIGNED	dim 1. Jacobs	TITLE GEO TO GI	st DATE10-	המשת המת הבת המת	
	2	(This space for Federal or Sta	e office use) ACC	EPTED FOR RECORD	
APPROVED I	BY	TITLE	DATE		
CONDITIONS	OF APPROVAL, IF ANY:			OCT 1 # 1984	

\*See Instructions on Reverse Side

NACOOL

RY SMM