Form 3162-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED				
Budget Bureau No. Expires: March	1004-0135			
Expires: March	31, 1993			

		Sold to a substitution of the substitution of	NM 015150		
		SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
	Do not use		1. 6.1		
	Do not use	Use "APPLICATION FOR PERMIT-" for such proposals	1 0 !		
		SUBMIT IN TRIPLICATE	7. IF UNIT OR CA, AGREEMENT DESIGNATION		
1.	TYPE OF WE		STOVE CANYON 8. WELL NAME AND NO.		
1.	OIL WELL		6. WELL NAME AND NO.		
2.	NAME OF OF		9. API WELL NO.		
	CONOCC	O INC.	30-045-29480		
3.			10. FIELD AND POOL, OR EXPLORATORY AREA		
		Drive, Ste. 100W Midland, Texas 79705-4500 (915-686-5424)	PENN/MISS WILDCAT		
4.		DF WELL (Footage, Sec., 1'., R., M., or Survey Description)	11. COUNTY OR PARISH, STATE		
	1940' FS	L & 1320' FWL, UNIT LETTER "K", SEC 01, T-27-N, R-08-W	SAN JUAN, NM		
12.		CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE	REPORT, OR OTHER DATA		
	·	TYPE OF SUBMISSION TYPE	OF ACTION		
	□ N	lotice of Interp ECEIVED Abandonment	Change of Plans		
	⊠s	Subsequent Recompletion	New Construction		
		Plugging Back	Non-Routine Fracturing		
	r		Water Shut-Off		
		Office Casing Casing Spud & casing report	Conversion to Injection		
		Other: Spud & casing report	Dispose Water (Note: Report results of multiple completion on Well Completion or		
13.	Describe Pro	posed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including es	Recompletion Report and Log Form.) timated date of starting any proposed work. If well is		
	directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)				
	10/30/97	MIRU.			
	10/31/97 Set 30" @ 40', 3-1/2" yards of Redi Mix Cement filled to surface.				
	11/08/97	Spudded well.			
	11/10/97 Ran 7 joints, set 20", 94#, K-55 BTC. Landed at 298'. Cement with 534 sx of Class B + 3% CaCl2 + .25#/sk Cello Flake. Displaced with 3.5 bbls of water, full muddy returns. Cement returns 20 bbls, 9.3 sx, floats held. Bumped plug at 11:35 a.m. on 11-10-97 with 300 psi.				
	11/16/97 Ran 28 joints 13-3/8", 61#, K-55 BTC, also ran 51 joints, 54.5#, K-55 BTC. Landed at 3350'. Cement with 1830 sks. 35/65 POZ + 8% Gel + 2% CaCl2 + 6.25#/sx Gilsonite + .25#/sx Cello Flake + 109.850% H20. Followed by 100 sx of Class B + .25#/sx Cello Flake + 46.34% H20. Displaced 512 bbls of H20. Muddy returns, cement returns 80 bbls. Floats held. Bumped plug at 21:23 p.m. on 11/17/97 with 1500 psi. 16 cent 1/jt every 2 nd jt from 3350' to 2063'. 12 cent 1/jt every 4 th jt from 2063' to surface.				
	Ran 179 joints 9-5/8", 47# L-80, LTC, landed @ 7508'. Cement with 1005 sks of 35/65 Class B + 8% Gel + .25#/sk Cello Flake + 8#/sk Kol Seal + 2% CaCl2. Followed by 125 sks of Class H + .4% CD-32 + .3% FL-52 + .15% SM + 2% CaCl2 + .25#/SK Cello Flake. Displaced w th 547 bbls. partial returns, no cement returns. Floats held. Bumped plug @ 07:00 a.m. on 11-27-97, w/ 2000 PSI. Did not circ. any fluid to surface. Cmt tops @ 3644'. By bond log.				
	01/16/98	(FURTHER CASING AND CEMENT INFORMATION WILL BE FORWARDED TO DEPTHS WILL BE REPORTED ON PENDING INFORMATION/NOTIFICATION FI STEVE MASON/BLM.)			
14.	I hereby cert	tify that the foregoing is true and correct			
	SIGNED	Sighting Almson as	Agent for Conoco Inc. DATE 01/16/97		
-	(This space	e for Federal or State office use)	AUSERI		
	A DDDO' T	ED BY	-		
			DATE 1998		
	Conditions of approval, if any:				
Tit	Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of the Street States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.				