

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

RECEIVED
99 APR 19 PM 12:19

070 FARMINGTON, NM

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
COLEMAN OIL & GAS, INC.

3. Address and Telephone No.
PO Drawer 3337, Farmington, NM 87499 (505) 327-0356

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1850' FNL & 790' FWL, Section 15, T26N, R12W

RECEIVED
APR 23 1999

OIL CON. DIV.
DIST. 3

5. Lease Designation and Serial No.
NM 33015

6. If Indian, Allottee or Tribe Name
Navajo (Surface)

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Barbara #1

9. API Well No.
30-045-29888

10. Field and Pool, or Exploratory Area
WAW Fruitland Sand - PC

11. County or Parish, State
San Juan County, NM

CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other see below

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SPUD WELL APRIL 12, 1999 @ 11:00AM. DRILLED 8 3/4" SURFACE HOLE FROM SURFACE TO 135 FT. GL. RAN 122.40 FT OF 7" 20# J-55 ST&C & SET @ 123.40 FT GL. CEMENTED W/ 50 SACKS CLASS B W/ 3% CACL & 1/4# PER SACK CELLOFLAKE. CIRCULATED 4 BBLs CEMENT TO RESERVE PIT. NIPPLED UP & PRESSURE TESTED BOP, MANIFOLD & CASING TO 600 PSI. DRILLED 6 1/2" TO 1400 FT GL. TD WELL @ 1400 FT GL. ON APRIL 14, 1999 @ 1:45PM. RAN 33 JTS 4 1/2" 10.50# ST&C J-55. LANDED CASING AT 1396.6 FT. GL. CEMENTED WITH 110 SACKS CLASS B W/ 2% METOSILICATE, 1/4# PER SACK CELLOFLAKE. TAILED WITH 50 SACKS CLASS B W/ 1/4# PER SACK CELLOFLAKE AND 2% CACL. CIRCULATED 8 BBLs CEMENT TO SURFACE PIT.

OPEN HOLE LOGS RAN SCHLUMBERGER LDT-CNT-GR-HCAL, AND AIT-GR-HCAL DATED 04/14/99.

14. I hereby certify that the foregoing is true and correct

Signed Michael T. Hanson (MICHAEL T. HANSON) Title ENGINEER Date 04/15/99

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side