

APPROVED
(April 1952)

JUN 12 1956

Budget Bureau NO. 42-K-309.3.
Approval expires 12-31-55.

(SUBMIT IN TRIPLICATE)

Indian Agency _____

Jicarilla

Allottee _____

Lease No. **Tribal #68**

(Orig. Sgd.)	J. V. [Signature]
ACTING DISTRICT ENGINEER	

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL _____	

RECEIVED
MAY 16 1956
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Indian _____, 19 **56**

Well No. **3-1** is located **1690** ft. from **[S]** line and **1690** ft. from **[W]** line of sec. **36**

15/4 N/4 **36** **28N** **3W** **S. 10. P. 1. N.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Niland **San Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~dark floor~~ **ungraded ground** above sea level is **7965** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

T.D. 606)⁰. Perf. 5913-3, 5950-34, 5960-63, 5969-74, 6010-20, 6024-34, 6040-44, w/3 shots/ft and free PL w/47,000 gals water only. SD 17000, avg 17000, Max 17000, Final 17000, standing 4000 in 5 minutes. I.R. 47.3 BPM. Perf. 5720-24, 5746-32, 5756-40, 5764-48, 5800-54, 5808-12, 5818-22, 5824-30, 5828-38 w/3 shots/ft., set SP @ 9890' and free Nanteco w/48,720 gals water only. SD 22000, avg 18900, Max 19000, Final 19000, standing 9000 in 5 min. I.R. 43 BPM. Retrieved SP. Perf. 5612-22, 5622-76, 5628-80, 5693-99, w/3 shots/ft., set SP @ 5700' and free ON w/47,000 gals water only. SD 20000, avg 18000, Max 19000, Final 19000, standing to 5000 in 5 minutes. I.R. 41 BPM. Cleaned out to T.D. and set 6013.02' of 2-1/8" OD 4.75 J-55 tubing w/perf. nipple, @ 6026.12'. Released rig @ 4:00 P.M. 3-17-56.

I understand that this plan of work must receive approval in writing by the Geological Survey before operation can be started.

Company **Pacific Northwest N.E. Corp.**
Northwest Production Corp.

Address **4132 W. Main,**
Farmington, New Mexico

By **Original signed by T. A. Dugan**

Title **District Engineer**

10-11-11

RECEIVED
U.S. DEPARTMENT OF
HARMONIC RECORDS

