


Section 26

(SUBMIT IN TRIPLICATE)

Indian Agency



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Jicarilla Apache

Allottee

Lease No. 240

990' FSL, 990' FW

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 18, 1962

Jicarilla 4-26

Well No. 5 is located 990 ft. from SW line and 990 ft. from SE line of sec. 26

SW of SW, Sec. 26
(1/4 Sec. and Sec. No.)

26N
(Twp.)

1W
(Range)

10PM
(Meridian)

Boulder-Mancos
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 7196 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mud logs; indicate points, and all other important proposed work)

Spudded well 8:45 AM, August 25, 1962. Drilled 12 1/2" hole to 139 feet. Landed & cemented 9-5/8", 36#, J-55, STAC new casing at 136.58 feet with 100 sx cement. Circulated estimated 45 sx cement to surface. WOC 10:15 PM, 8-25-62. After WOC for total of 2 1/2 hours, tested 9-5/8" casing to 1000 psi for 30 minutes, OK. Drilled ahead in 8-3/4" hole to depth of 3465 feet. Logs were run. Landed & cemented 7", 20#, J-55, STAC casing at 3463.73 feet with 150 sx cement. WOC 3:30 AM, 9-4-62. After WOC 2 1/2 hours, tested 7" casing to 1500 psi for 30 minutes, OK. Drilled 6 1/2" hole to total depth of 3933 feet, using air drilling equipment. Ran logs. Ran & landed 2-3/8" production tubing at 3394 feet. Released rotary rig 7:30 PM, September 8, 1962. Now preparing to test well for potential.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Company of Texas, A Division of California Oil Company

Address Dwyer "S"

Mouhans, Texas

By J. L. Rowland J. L. Rowland

Title District Engineer

RECEIVED
SEP 25 1962
OIL CON. COM.
DIST. 2