

SF-079051-B

San Juan 28-6 Unit

105

Basin Dakota

35-28N-6W

N4PM

Rio Arriba

New Mexico

6636.5' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-28-64 Rigged up completion rig, drld DV tools, CO to 7553'. Tested csg to 4000#, held OK. Displaced hole w/1% Potassium Chloride wtr. Spotted 500 gals 7 1/2% acid on bottom.

7-29-64 Ran correlation log & perf 7444-58 w/1 JPF. Pumped acid. FBD 1500#, pumped 7 BPM @ 1800#. Perf 7436-42, 7508-14 & 7536-40 w/1 JPF. Pumped 500 gals 15% acid down csg w/14 balls to seal perfs 7444-58'. SNF w/20,000# 20-40 sd, 37,300 gals 1% Potassium Chloride wtr w/7# J-2/1000 gals, 45,000 gals total wtr. TP 4000#, ATP 24.6 BPM. SI 2400#, 5 MSI 2100#. Perf 7316-19, 7338-44, 7352-58 & 7368-71 w/2 JPF. FBD 1800#, pumped 500 gals 15% acid ahead of frac. SNF w/20,000# 40-60 sd, 32,300 gals treated wtr; 36,000 gals total wtr. TP 4000#, rate 32 BPM. SI 1900#, 5 MSI 1800#, SI 2 hours. Well unloaded. Ran production string - 238 jts 7500' 2" EUE tbg w/1' nipple, total tbg 7501' landed @ 7512'. Rig released @ 7 AM 7/29/64. Wet gauge 1,300 MCF est. Blowing well to clean up prep to SI for test.

18. I hereby certify that the foregoing is true and correct.

SIGNED JOHN T. HAMPTON

TITLE

Manager

DATE

8/10/64

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.