2007	l - Phill l - EPNG l - File	(Farmi	ngton	MULT							Form C	
	ial 🗶											
	any <b>Pacif</b>										9-32	
	7"											
asiı	ng 5# W	/t	I	.D	Se	et at	<b>6231</b> Pe	rf	658	_To	61.98	
ubi	ng <b>2</b> * W	/t•	I	.D	Se	et a.t_60	18.38' Pe	rf	<del></del>	To		
as I	Pay: From_		_To		L		cG		<del></del>	Bar.Pr	ess. 12.0	
rodi	cing Thru:	Cas	ing		Tu	bing	XX	Type We	ell <b>8</b>	agi e		
ate	of Complet	ion:			Packe	r_ No	Sin	gle-Brade Reservo	enhead-G.	G. or	G.O. Dual	
							ED DATA					
este	ed Through	( Paracycae	- <del> </del>	Choke)	(a) Gradus and				Туто Топ			
			Low Da				( m)					
T	PRESERVE	(Chol	ke)	Press	· Diff.	Temp.		Data Temp.	Casing D		Duratio	
	Size	(Ocoo Siz		psig	h <sub>w</sub>	°F.	psig	°F.	psig	°F∙	of Flo	
Ŧ	2*	2//		260		68	1155		1151		Shut-in	
		3/4		220		<u> </u>	350	68	81.9		3 hrs.	
				,								
-	(24-Hour) -		hwp	f	psia	Factor F <sub>t</sub>		Factor Fg	Factor F <sub>pv</sub>		Q-MCFPD @ 15.025 psi	
#	14.1605				20%	•9924		.9258	1.04	2	4907	
								<del></del>				
/it	quid Hydroc y of Liquid	l Hydro	carbo			cf/bbldeg.		Speci	fic Gravit		rator Gas ring Fluid	
·Ì	Pw Pt (psia)	Pt <sup>2</sup>	Fc	2	$(F_cQ)^2$	(F.	Q) <sup>2</sup> e-s)	P <sub>w</sub> 2	$P_c^2 - P_w^2$		Pw Pc	
	831		1					690,6	671.3		w P <sub>c</sub> 2.029	
	NO16	<b>30</b> 000	1 2:									
L												
(PA)		dific	t Bro	west P		Corp.	n75 = : Mexico est Engin					
NT NES	1A					REMA	DKC			FFIN		

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ( $P_{\rm W}$ ). MCF/da. @ 15.025 psia and 60° F.
- P<sub>c</sub>= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- $\mathbb{P}_{w}^{\perp}$  Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- $P_{f}$  Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- $F_t$  Flowing temperature correction factor.
- F<sub>DV</sub> Supercompressability factor.
- n \_ Slope of back pressure curve.
- Note: If  $P_{\mathbf{W}}$  cannot be taken because of manner of completion or condition of well, then  $P_{\mathbf{W}}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\mathbf{t}}$ .

ALTEC (	DISTRI	T OFFI	CE
No. Copies Re	goer no	3	
	TRE	iTion	
* - * - * - * - * - * - * - * - * - * -		Fig. Otal Isher	
daer que		3 3	
The search of the second			1
ringalis (Mind		A refer to service a page	
Just Lancons.	. i.,		
0 2 C 3			
ीरताम हाउच्यान	Mar. s		
हैंसेक	1	1	-