NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Poo	1 Blanco			F	ormation	Mesa	Verde		County	Rio Ar	riba
Ini	tial X		Annu	21 <u> </u>		Spe	cial		_Date of	Test	7-25-57
Com	pany Pacifi	le North	west	Pipeli	ne	Lease_	San Juan	28-4	Wel	1 No	12-33
Uni	t <u>K</u>	Sec 33	Tw	. 28 ≡	Rg	e. 4W	Pur	chaser_ no	t connecte	ed.	
Cas	ing 5½ V	Wt	I	.D	Se	t at	6629 P	erf. 6034		То	6554
Tub	ing 2 3/8 V	Nt	I.	.D.	Se	t at	6511 P	erf		То	
Gas	Pay: From	6034	To_6	5554	L		xG .650			Bar.Pre	ess. 12
Pro	ducing Thru	: Casi	ng		Tu	bing_	X	Туре We	:11 81 n	gle	
Dat	e of Complet	cion:			Packe	r	Si	ngle-Brade Reservo	enhead-G. oir Temp	G. or C	G.O. Dual
							VED DATA				
Test	ted Through	XXXXXX	z) (c	Choke)	(Mexico)	Shut I	n 7days		Type Tap	s	
			ow Da					g Data	Casing D		T
No.	(Prover) (Line)	(Choke	e) ce)	Press.	Diff.	Temp.		. Temp.	Press.	Temp.	Duration of Flow
	Size	Siz		psig	h _w	°F.		°F.	psig	°F∙	Hr.
SI l.		3/4		218		610	1025 218	610	691		3
2.											
3 .		 					+		<u> </u>		
5.											
					1	ביורש רג	I CITT A TTO	MS			
Coefficient					FLOW CALCULATIONS Pressure Flow Temp. Gravity				Compress. Rate of Flow		
No.	(2) 11	>	1	— I		Fa	ctor	Factor	Facto		Q-MCFPD
_	(24-Hou	$\frac{\mathbf{r}}{\sqrt{2}}$	/ n _w p)f				Fg	Fpv		@ 15.025 psia
2. 3.	12.3650			23	0	,9990	-	.96 0 8	1.0	22	2790
3.											
**											
<u>'• 1</u>			<u>.</u>		PRI	ESSURE	CALCUIAT:	IONS		<u> </u> -	
	iquid Hydro ty of Liqui					cf/bbl					rator Gas ring Fluid
	oy or frique	u nyurot	(1	e ⁻⁵)		deg	•	P _C	116 Gravi	P2 _P2	1366.6
								U			
Т	$P_{\mathbf{w}}$	_	Т —				$\overline{}$	703		1	
10.		$P_{\mathbf{t}}^{2}$	Fc	Q	$(F_cQ)^2$	(F _c Q) ² 1-e ^{-s})	703 P _w 2	$P_c^2 - P_w^2$		P _W
_	Pt (psia)		↓			()	T-e_s)	1.51 -	0==	P	W
2.			<u> </u>	+				h9h.2	872.4	 	1.57
-		·	├ -							1	
									<u> </u>	15	
bsc	lute Potent	ial:_3,	80h			MCFPD	; n	5/ 1.3958	/	KUL	ШУц
MUUL	ANY Part MESS hos 1	Northwe	est I	Mpelin	e Corpo	ration	ud oc				
IGEN	IT and TITLE	C. R.	Va eme		· ·	Well To	et Engine	MOT		OU OO	W con f
TIN	IESSED) N. COM. }
OMF	PANY					ייזרו	MADNO			الا	ស.ខ ្ល
						KE	MARKS			Bridge Services	Market and a second

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_w) . MCF/da. @ 15.025 psia and 60° F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- F_g : Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{nv} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to P_{+} .

OIL CONSERVATION COMMISSION									
AZTEC DISTRICT OFFICE									
No. Copies Received ろ									
DISTRIBUTION									
	NO. FURNISHED								
Operator									
Santa Fe	/								
Proration Office									
State Land Office									
U. S. G. S.	/								
Transporter									
File	1	-							