Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

| FORM APPROVED |        |         |         |  |
|---------------|--------|---------|---------|--|
| Budget I      | Burcau | No. 1   | 004-013 |  |
| Expin         | es: Ma | urch 31 | , 1993  |  |

5. Lease Designation and Serial No.

| SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to deepen or reentry to a different reservo  Use "APPLICATION FOR PERMIT—" for such proposals | Jic. Tribal Contract  6. If Indian, Allottee or Tribe Name  Jicarilla |
|---|---|
| SUBMIT IN TRIPLICATE  | 7. If Unit or CA, Agreement Designation                               |
| 1. Type of Well  [X] Oil Gas Well Well Other P&A  2. Name of Operator   | 8. Well Name and No.  |
| Dugan Production Corp.  3. Address and Telephone No.  | Boulder 3 9. API Well No.   |
| P.O. Box 420, Farmington, NM 87499 (505) 325-1821  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)   | 30-039-07253  10. Field and Pool, or Exploratory Area  Boulder Mancos |
| 330' FSL - 390' FWL<br>Sec. 23, T28N, R1W, NMPM   | II. County or Parish, State Rio Arriba, NM                            |
| 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE BED   |   |

NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION Abandonment Change of Plans Recompletion **New Construction** 

SEP1 51993

Plugging Back

Non-Routine Fracturing Water Shut-Off Conversion to Injection

Dispose Water (Note: Report results of multiple completion on Well

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged well as follows:

Perforate blow Gallup a 41451.

- 2. Spot 39 cu. ft. Class B cement with 2% CaCl<sub>2</sub> at 4150'. Displace to 3945'. Gallup plug 3945' -
- Spot 16 cu. ft. Class B cement across liner top @ 3627' from 3677' 3577'.

Spot 34 cu. ft. Class B cement plug across Mesa Verde 3010' - 3110'.

Perforate Pictured Cliffs 2 805'.

Spot 163 cu. ft. Class B + 4% gel cement 2 817.

Displace cement to 473'. Pictured Cliffs, Fruitland, Ojo Alamo plug 473' - 805'.

8. Perforate below surface casing 2 1831.

Cement down 7<sup>™</sup> casing out bradenhead to surface with 117 cu. ft. Class B + 4% gel cement. Surface plug 0' - 183'.

Job complete 6-30-93.

| 4. I hereby certify that the foregoing is true and correct                                   |   |                      |
|--|---|----------------------|
| Signed John alekanoan  | Tide <u>Operations Manager</u>                    | Date7/6/93           |
| (This space for Federal or State office use)  SHIRLEY MONDY  Conditions of approval, if any: | Acting AREA MANAGER Tide RIO PUERCO RESOURCE AREA | SEP 1 0 1933<br>Date |

Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements