

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Blanco Formation Mesa Verde County Rio Arriba  
Initial XX Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 5/29/57  
Company Pacific Northwest Pipeline Corp. Lease 28-4 Well No. 1131  
Unit G Sec. 31 Twp. 28N Rge. 4W Purchaser Not Connected  
Casing 5 1/2 Wt. \_\_\_\_\_ I.D. \_\_\_\_\_ Set at 4456 Perf. 5998 To 6536  
Tubing \_\_\_\_\_ Wt. \_\_\_\_\_ I.D. \_\_\_\_\_ Set at \_\_\_\_\_ Perf. \_\_\_\_\_ To \_\_\_\_\_  
Gas Pay: From \_\_\_\_\_ To \_\_\_\_\_ L \_\_\_\_\_ xG .650 -GL \_\_\_\_\_ Bar.Press. 12  
Producing Thru: Casing \_\_\_\_\_ Tubing XX Type Well Single  
Single-Bradenhead-G. G. or G.O. Dual  
Date of Completion: \_\_\_\_\_ Packer \_\_\_\_\_ Reservoir Temp. \_\_\_\_\_

## OBSERVED DATA

Tested Through (Proven) (Choke) (Meter) SI 7 days Type Taps \_\_\_\_\_

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						1033		1126		
1.		3/4	228		70	228	70	745		3
2.										
3.										
4.										
5.										

## FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	14.1605		240	.9905	.9608	1.022	3305
2.							
3.							
4.							
5.							

## PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)  
Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> 1138 P<sub>c</sub><sup>2</sup> 1295.0

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	$\frac{757}{P_w^2}$	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	$\frac{P_w}{P_c}$
1.						573.0	722.0		1.79
2.									
3.									
4.									
5.									

Absolute Potential: 5,114 MCFPD; n .75/ 1.5474

COMPANY Pacific Northwest Pipeline Corporation

ADDRESS \_\_\_\_\_

AGENT and TITLE C. R. Wagner Well Test Engineer

WITNESSED \_\_\_\_\_

COMPANY \_\_\_\_\_

REMARKS \_\_\_\_\_



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- $Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.
- $P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia
- $P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if  
flowing through casing.) psia
- $P_f$  = Meter pressure, psia.
- $h_w$  = Differential meter pressure, inches water.
- $F_g$  = Gravity correction factor.
- $F_t$  = Flowing temperature correction factor.
- $F_{pv}$  = Supercompressability factor.
- $n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .

<b>OIL CONSERVATION COMMISSION</b>		
<b>AZTEC DISTRICT OFFICE</b>		
No. Copies Received <u>3</u>		
<b>DISTRIBUTION</b>		
	NO. FURNISHED	
Operator		
Santa Fe	/	
Proration Office		
State Land Office		
U. S. G. S.	/	
Transporter		
File	/	✓