(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Sauter La
Lease No.	078498
Sen .	Auan 28-7 Unit 8-001-459

NOTICE OF INTENTION TO CHANGE PLANS. NOTICE OF INTENTION TO TEST WATER SHIT-OFF. NOTICE OF INTENTION TO REDURLL OR REPAIR WELL. NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING. SUBSEQUENT REPORT OF REDURLLING OR REPAIR. SUBSEQUENT REPORT OF REDURLLING OR REPAIR. SUBSEQUENT REPORT OF REDURLLING OR REPAIR. SUBSEQUENT REPORT OF REPORT OR REPAIR. SUBSEQUENT REPORT OF REPORT OR REPAIR. SUBSEQUENT REPORT OR ACIDIZE. SUBSEQUENT REPORT OR REPAIR. SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF SUBMILLENCE. SUBSEQUENT REPORT OF SUBMILLENCE. SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF SUBMILLENCE. SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF SUBMILLENCE. SUBSEQU	NOTICE OF INTENTION TO DRILL.	SUBSEQUENT REPORT OF WATER COMME	94
MOTICE OF INTENTION TO REDRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 22 19.5 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 22 19.5 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 22 19.5 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 22 19.5 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 22 19.5 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 22 19.5 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 22 19.5 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 22 19.5 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 23 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 23 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 23 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 24 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 25 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 25 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 25 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 25 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 25 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) MARCH 25 (INDICATE ABOVE BY DATA) MARCH 25 (INDICATE ABOVE BY DATA) MARCH 26 (INDICATE ABOVE BY DAT	NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT NETOKI OF WAIER SHUT-OFF	<u></u>
Subsequent report of Re-Drill no Repair well. NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR. SUBSEQUENT REPORT OF RE-DRILLING. SUBSEQUENT REPORT OF REPORT OR REPAIR. SUBSEQUENT REPORT OF RE-DRILLING. SUBSEQUENT REPORT OF RE	NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUPEROUTALE DESCRIPTION OF SHOOTING OR ACIDIZING	
Subsequent report of Abandonment Supplementary well history. Supplementar	NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSTOLEMENT OF ALTERING CASING	
Supplementary well history. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 22 [One of its located 1700 ft. from the line and 1700 ft. from the line of sec. 32 [One of section of section of section of section of section of section of the derick floor above sea level is section of the derick floor floor floor floor floor above sea level is section of the derick floor floo	NUTICE OF INTENTION TO SHOOT OR ACIDIZE	SUPSECUENT PERSON	
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 22 [7] [8] [8] [8] [8] [9] [9] [10] [11] [12] [12] [13] [14] [15] [15] [15] [16] [16] [17] [18	NOTICE OF INTENTION TO PULL OR ALTER CASING.	CIIDDI EMENTADO MENT	
/ell No. 69 is located 1700 ft. from [N] line and 1700 ft. from [E] line of sec. 32 ## Section 32 (K Sec. and Sec. No.) (Rup.) (Range) ## ##.M.P.M. (County or Subdivision) Meridian Meridian (Richard County or Subdivision) Tt. DETAILS OF WORK ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment ing points, and all other important proposed work) 3-9-57. Total hepth hy70': Run 12 joints 5-1/2', 15-3f, J-55 casing liner from h592 to h964' with 50 sacks regular counts, 50 sacks Posmix, hy gal, 1/hs/sack flucele followed by 50 sacks regular counts. Held 1000 for 30 minutes. Top of coment by temperature survey at h592'. Application of work must receive approval in writing by the Geological Curvivity properations may be commenced. In Paso Satural Gas Company Tess Box 997	NOTICE OF INTENTION TO ABANDON WELL		
Section 32 See H.M.P.M.	(INDICATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
Well No. 69 is located 1700 ft. from No. 69 Inne and 1700 ft. from E Inne of sec. 32 Inne section 32 288 The Section 32 Inne of sec. 32 Inne section 33 Inne section 34 Inne section 35 In		March 22	10 5
County or Subdivision) County or Subdivision County or Subdivision) County or Subdivision County or Su	/ell No. 69 is located 1700 ft. from	$\{m, N\}$ line and 1700 ft. from $\{E\}$ line of so	ec. 32
Rispico (Field) Rio Arriba (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 6057 At DETAILS OF WORK ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement in points, and all other important proposed work) 3-9-57. Total Bepth 1970: Ram 12 joints 5-1/2', 15.5%, J-55 casing liner from 1592 to 1964: with 50 sacks regular canast, 50 sacks Formix, 14 gal, 1/14/sack flocele followed by 50 sacks regular canast. Beld 1000f for 30 minutes. Top of cement by temperature survey at 1592'. MAR 26 1957 understand that this plan of work must receive approval in writing by the Geological Survey By operations may be commenced. The pass setural Gas Company Tess Box 997 Farmington, Hear Mention	EE Section 32 201	TV H.N.P.N.	
(Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 6057 The DETAILS OF WORK ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement ing points, and all other important proposed work) 3-9-57. Total Bepth 1970. Ram 12 joints 5-1/2, 15.54, 3-55 casing liner from 1592 to 1964. With 50 sacks regular cament, 50 sacks Formix, 15 gal, 1/1/4/sack flocele followed by 50 sacks regular cament. Beld 1000f for 30 minutes. Top of cement by temperature survey at 1592. Top of cement by temperature survey at 1592. The sacks regular cament. The sacks regular cament. The sacks regular cament. The sacks regular cament. The sacks flocele followed by 50 sacks regular cament. The sacks regular cament. The sacks regular cament. The sacks regular cament. The sacks flocele followed by 50 sacks regular cament. The sacks regular cament. The sacks regular cament. The sacks flocele followed by 50 sacks regular cament. The sacks regular cament. The sacks flocele followed by 50 sacks regular cament. The sacks flocele followed by 50 sacks regular cament. The sacks regular cament for the sacks flocele followed by 50 sacks regular cament. The sacks flocele followed by 50 sacks regular cament. The sacks flocele followed by 50 sacks regular cament. The sacks flocele followed by 50 sacks regular cament. The sacks flocele followed by 50 sacks regular cament. The sacks flocele followed by 50 sacks flocele fl	Plana	(Range) (Meridian)	
DETAILS OF WORK ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement ing points, and all other important proposed work) 3-9-57. Total Bepth 4970: Ram 12 joints 5-1/2', 15-54, J-55 casing liner from 4592 to 4964. With 50 sacks regular commat, 50 sacks Posmix, 44 gal, 1/44/sack flocele followed by 50 sacks regular commat. Beld 1000f for 30 minutes. Top of commat by temperature survey at 4592'. MAR 26 1957 understand that this plan of work must receive approval in writing by the Geological curve 1890 operations may be commenced. Passo Matural Gas Company Paramington. New May 1691 1997 Farmington. New May 1691 1997 Farmington. New May 1691 1997 ORIGINAL CICALED E 141 BOYT	(77) 13)	(or Subdivision)	
ress Box 997 Farmington, New Martine ORICINAL CICAED E W. DOVS	ate names of and expected depths to objective sands; show size ing points, and all of 3-9-57. Total Depth 4970 ** Ran 12 joints 5-1/2* 15 5-2 7 5-3	zes, weights, and lengths of proposed casings; indicate mudding other important proposed work)	
ress Box 997 Farmington, New Montes ORIGINAL CICNED E W DOVS	3-9-57. Total Depth 4970. Ram 12 joints 5-1/2, 15.54, J-5; with 50 sacks regular coment, 50 followed by 50 sacks regular coment.	zes, weights, and lengths of proposed casings; indicate mudding other important proposed work) 5 casing liner from 4592 to 4964;	
Farmington, New Montes ORIGINAL CICARD E W DOUG	ate names of and expected depths to objective sands; show sizing points, and all of 3-9-57. Total Depth 1970. Ran 12 joints 5-1/2, 15.54, J-5; with 50 sacks regular coment, 50 followed by 50 sacks regular coment. Bald 1000f for 30 minutes. Top of coment by temperature surrective approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that this plan of work must receive approval in winderstand that the plan of work must receive approval in winderstand that the plan of work must receive approval in winderstand that the plan of work must receive approval in winderstand that the plan of work must receive approval in winderstand that the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receive approval in winderstand the plan of work must receiv	zes, weights, and lengths of proposed casings; indicate mudding other important proposed work) 5 casing liner from 4592 to 4964. 5 casing liner from 4592 to 4964. 5 casing liner from 4592 to 4964. 6 casing liner from 4592 to 4964.	cele
Parmington, New Nextco By ORIGINAL SIGNED F. W. BOY'S	J-9-57. Total Depth 1970. Ran 12 joints 5-1/2, 15.5#, J-5; with 50 sacks regular coment, 50 followed by 50 sacks regular coment. Bald 1000 for 30 minutes. Top of coment by temperature sure understand that this plan of work must receive approval in v	zes, weights, and lengths of proposed casings; indicate mudding other important proposed work) 5 casing liner from 4592 to 4964. 5 casing liner from 4592 to 4964. 5 casing liner from 4592 to 4964. 6 casing liner from 4592 to 4964.	cele
	ate names of and expected depths to objective sands; show size ing points, and all of 3-9-57. Total Depth 1970. Ran 12 joints 5-1/2, 15.54, J-5; with 50 sacks regular coment, 50 followed by 50 sacks regular coment. Beld 1000f for 30 minutes. Top of coment by temperature surrective approval in with the plan of work must receive approval in with the p	zes, weights, and lengths of proposed casings; indicate mudding other important proposed work) 5 casing liner from 4592 to 4964. 5 casing liner from 4592 to 4964. 5 casing liner from 4592 to 4964. 6 casing liner from 4592 to 4964.	cele



OMETHAL SYSTEM FLAV ROTT