
## Form 9-881 a (Feb. 1951)



## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

| Budget B<br>Approval |  |  |
|----------------------|--|--|
|                      |  |  |

Land Office Banta Fe

Lease No. 078496-A

Unit San Juan 28-7 Unit 14-08-001-459

| NOTICE OF INTENTION TO DRILL   | SUBSEQUENT REPORT OF WATER SHUT-OFF.  |
|--|---|
| NOTICE OF INTENTION TO CHANGE PLANS  |   |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF   | SUBSEQUENT REPORT OF ALTERING CASING  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.  | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE  | SUBSEQUENT REPORT OF ABANDONMENT.   |
| NOTICE OF INTENTION TO PULL OR ALTER CASING  | WAV and   |
| NOTICE OF INTENTION TO ABANDON WELL  |   |
| (INDICATE ABOVE BY CHEC  | CK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  May 16 19 5   |
|  |   |
| 'ell No. 91 (PM) is located 836 ft   | t. from Siline and 1544 ft. from Strine of sec. 34  |
| MR Sec. 34 28N (1/2 Sec. and Sec. No.) (Twp.)  | 7W N.M.P.M.   |
|  |   |
|  | Rio Arriba New Mexico   |
| Late names of and expected depths to objective sands; ing points,  | sea level is 6089 ft.  DETAILS OF WORK  |
| he elevation of the derrick floor above  Leate names of and expected depths to objective sands; ing points, ing points, ing points, in 4-24-58.  Total Depth 175'.   | (County or Subdivision) (State or Territory)  sea level is 6089 ft.  DETAILS OF WORK  show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come and all other important proposed work)  |
| The elevation of the derrick floor above  It is take names of and expected depths to objective sands; ing points,  Spud date 4-21-58.  On h-24-58. Total Depth 175'.  Ran 4 joints 10 3/4", 32.75#, 8  | (County or Subdivision)  sea level is 6089 ft.  DETAILS OF WORK  show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comes and all other important proposed work)  spinal weld casing (163°) set at 174° with 200  |
| he elevation of the derrick floor above  Late names of and expected depths to objective sands; ing points, ing points, ing points, ing points, ing points, in 4-24-58. Total Depth 175'. Itan 4 joints 10 3/4", 32.75#, sacks regular cement circulated  | (County or Subdivision)  sea level is 6089 ft.  DETAILS OF WORK  show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comes and all other important proposed work)  spinal weld casing (163°) set at 174° with 200  |
| The elevation of the derrick floor above  Litate names of and expected depths to objective sands; ing points, ing  | (County or Subdivision)  sea level is 6089 ft.  DETAILS OF WORK  show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comes and all other important proposed work)  spinal weld casing (163°) set at 174° with 200  |
| he elevation of the derrick floor above  Late names of and expected depths to objective sands; ing points, in h-24-58. Total Depth 175'. Ran 4 joints 10 3/4", 32.75#, sacks regular cement circulated   | (County or Subdivision)  sea level is 6089 ft.  DETAILS OF WORK  show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comes and all other important proposed work)  spinal weld casing (163') set at 174' with 200 d to surface.  |
| he elevation of the derrick floor above  Late names of and expected depths to objective sands; ing points, ing points, ing points, ing points, ing points, in 4-24-58. Total Depth 175'. Itan 4 joints 10 3/4", 32.75#, sacks regular cement circulated  | (County or Subdivision)  sea level is 6089 ft.  DETAILS OF WORK  show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come and all other important proposed work)  spinal weld casing (163') set at 174' with 200 it o surface.   |
| he elevation of the derrick floor above  Late names of and expected depths to objective sands; ing points, ing points, ing points, ing points, in 4-24-58. Total Depth 175'. Ian 4 joints 10 3/4", 32.75#, sacks regular cement circulated   | (County or Subdivision)  Sea level is 6089 ft.  DETAILS OF WORK  Is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemes and all other important proposed work)  Spinal weld casing (163') set at 174' with 200 it o surface.   |
| he elevation of the derrick floor above  Itate names of and expected depths to objective sands; ing points, ing po | (County or Subdivision)  sea level is 6089 ft.  DETAILS OF WORK  show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemes and all other important proposed work)  spinal weld casing (163') set at 174' with 200  to surface.  MAY Z 1 1558  CON. COM.  |
| The elevation of the derrick floor above  Late names of and expected depths to objective sands; ing points, ing po | (County or Subdivision)  Sea level is 6089 ft.  DETAILS OF WORK  Is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comes and all other important proposed work)  Spinal weld casing (163') set at 174' with 200 it to surface.  MAY 211358  CON COM.  Sproval in writing by the Geological Survey before operations may be commenced.         |
| Itate names of and expected depths to objective sands; ing points, spud date 4-21-58.  On 4-24-58. Total Depth 175'.  Ran 4 joints 10 3/4", 32.75#, seacks regular cement circulated Held 500# for 30 minutes.  I understand that this plan of work must receive approximately company.  | (County or Subdivision)  Sea level is 6089 ft.  DETAILS OF WORK  Is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comes and all other important proposed work)  Spinal weld casing (163') set at 174' with 200 to surface.  MAY 21358  COMPANY   |
| The elevation of the derrick floor above  Itate names of and expected depths to objective sands; ing points,  Spud date 4-21-58.  On 4-24-58. Total Depth 175'.  Ran 4 joints 10 3/4", 32.75%, sacks regular cement circulated  Held 500% for 30 minutes.  | sea level is 6089 ft.  DETAILS OF WORK  show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come and all other important proposed work)  spiral weld casing (163') set at 174' with 200 d to surface.  MAY 24 1358  CON. COM.  ST. 3  Deproval in writing by the Geological Survey before operations may be commenced.  ORIGINAL SIGNED A.M. SMITH |