

3- N.M.O.C.C.  
1- EPNG (Galloway)  
1- L.G. Truby  
1- W.R. Johnston  
1- file

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Blanco Formation Mesaverde County Rio Arriba  
Initial XX Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 4-2-57  
Company Pacific Northwest Lease 28-5 Well No. 24-34  
Unit A Sec. 34 Twp. 28N Rge. 5W Purchaser not connected  
Casing 5 1/2 Wt. \_\_\_\_\_ I.D. \_\_\_\_\_ Set at 5985 Perf. 5906 To 5372  
Tubing 2 Wt. \_\_\_\_\_ I.D. \_\_\_\_\_ Set at 5895 Perf. \_\_\_\_\_ To \_\_\_\_\_  
Gas Pay: From \_\_\_\_\_ To \_\_\_\_\_ L \_\_\_\_\_ xG .650 -GL \_\_\_\_\_ Bar.Press. 12  
Producing Thru: Casing \_\_\_\_\_ Tubing XX Type Well single  
Single-Bradenhead-G. G. or G.O. Dual \_\_\_\_\_  
Date of Completion: \_\_\_\_\_ Packer no Reservoir Temp. \_\_\_\_\_

OBSERVED DATA

Tested Through (Packer) (Choke) (Packer) 7 days Type Taps \_\_\_\_\_

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						436		1140		
1.		3/4	186		640	186	640	647		3
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w p_f}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	14,1695		198	.9962	.9608	1.019	2735
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)  
Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> 1152 P<sub>c</sub><sup>2</sup> 1,327,104

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>c</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	659 P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> P <sub>c</sub>
1.						434,281	892,823		1.49
2.									
3.									
4.									
5.									

Absolute Potential: 3,688 MCFPD; n .75/ 1.3486  
COMPANY Pacific Northwest Pipeline Corp.  
ADDRESS 405 1/2 West Broadway, Farmington, New Mexico  
AGENT and TITLE C.R. Wagner - Well Test Engineer  
WITNESSED R.A. Ulrich - Engineer  
COMPANY El Paso Natural Gas Company

REMARKS



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

$Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.

$P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia

$P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

$P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

$P_f$  = Meter pressure, psia.

$h_w$  = Differential meter pressure, inches water.

$F_g$  = Gravity correction factor.

$F_t$  = Flowing temperature correction factor.

$F_{pv}$  = Supercompressability factor.

$n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received		3
DISTRICT NO.		
DATE		
Operator		
Per. No.	1	
Production Office		
Santa Fe Land Office		
U. S. G. S.	1	
Transporter		
File	1	✓