

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
990' FSL, 990' FWL, Sec. 29, T-28-N, R-4-W, NMPM

5. Lease Number
NM-03863

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 28-4 Unit

8. Well Name & Number
San Juan 28-4 U #15

9. API Well No.
30-039-07293

10. Field and Pool
Blanco Mesaverde

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

7-7-95 MIRU. ND WH. NU BOP. TOOH w/206 jts 2 3/8" tbg. TIH w/5 1/2" gauge ring to 6270'. POOH. TIH w/5 1/2" cmt retainer, set @ 6252'. PT tbg to 1000 psi, OK. Establish injection. Plug #1: pump 58 sx Class "B" cmt below cmt retainer into Mesaverde perms & 43 sx Class "B" cmt above cmt retainer, TOC @ 5872'. TOOH to 4452' SD for weekend.

7-10-95 Load csg w/114 bbl wtr. PT csg to 500 psi, OK. Plug #2: pump 106 sx Class "B" cmt inside csg @ 3906-4452'. TOOH to 3789'. Plug #3: pump 73 sx Class "B" cmt inside csg @ 3464-3784'. TIH w/7 5/8" gauge ring to 2350'. Perf 3 sqz holes @ 2383'. POOH. Load hole w/8 bbl wtr. Attempt to establish injection. Well locked up. Perf 3 sqz holes @ 2333'. Establish injection. TIH w/7 5/8" cmt retainer, set @ 2274'. Establish injection. Plug #4: pump 49 sx Class "B" cmt outside csg below cmt retainer, 10 sx Class "B" cmt on top of cmt retainer. TOC @ 2229'. POOH. TIH, perf 3 sqz holes @ 225'. POOH. Establish circ out bradenhead w/23 bbl wtr. Plug #5: pump 158 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. SDON.

7-11-95 ND BOP. Cut off WH. Pump 9 sx Class "B" cmt to fill 10 3/4 x 7 5/8" csg. Install dry hole marker w/11 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 7-11-95.

I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 7/18/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

APPROVED

MMCO

JUL 21 1995
[Signature]