


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 077520
Unit San Juan 28-5



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Water Fran.</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 5, 1960

Well No. 44 (ND) is located 340 ft. from S line and 890 ft. from W line of sec. 27

SW/4 SW/4 Sec. 27 28 N 5 W T.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco M.V. Dakota Wildcat Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6775 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

9-15-60 Total Depth 8180. C.O.F.D. 8157. Water fractured Dakota perforated int. 7934-70; 7975-82; 7994-8010; 8180-85 with 42,115 gallons water and 40,000 # sand. Breakdown pr 2800 #, maximum pr. 3700 #, avg. tr. pr. 2900 #. Injection rate 39.3 B.P.M. Flush 13,000 gallons.
9-18-60 Total Depth 8180. Temporary Bridge Plug at 7950. Water fractured Graneros perforated intervals 7812-80; 7906-18 with 41,239 gallons water and 40,000 # sand. Breakdown pr. 1900 #, max. pressure 2800 #, avg. tr. pr. 2400 #. Injection rate 38.6 B.P.M. Flush 13,000 gallons.
9-21-60 Total Depth 8180. Temporary Bridge Plug at 7750. Water fractured Point Lookout perforated intervals 5762-63; 5834-42; 5856-63; 5868-74; 5880-83; 5898-5904 with 51,396 gallons water and 50,000 # sand. Breakdown pr. 700 #, max. pr. 3400 #, avg. tr. pr. 2500 #. Injection rate 59.7 B.P.M. Flush 9912 gallons.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 990
Farmington, New Mexico

Original Signed By: D. H. Oheir
By _____

Title Petroleum Engineer

