

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SW/4 NW/4 1750' FNL & 560' FWL
Sec. 23, T28N, R1W, NMPMFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

Jic. Tribal Contract #241

6. If Indian, Allottee or Tribe Name

Jicarilla

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Boulder 2

9. API Well No.

30-039-07296

10. Field and Pool, or Exploratory Area

Boulder Mancos

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒
- Notice of Intent
-
- ☐
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☒
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☐
- Other _____
-
- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug by spotting Class B + 6% gel plugs as follows:

1. Gallup @ 4045', plug 3995-4095 inside 4½".
2. Mancos 3340 and 4½" liner top @ 3356', plug 3290-3390 inside 4½" and 7"
3. Mesa Verde @ 2878, plug 2828-2929 inside 7".
4. Perforate 7" @ 208', cement to surface inside and outside 7".

Spot plugs with 8.34 lb./gal., 40 sec./qt. vis. mud. Virgin bottom hole pressure in the Gallup was 425 psi. This weight mud will provide adequate well control.

14. I hereby certify that the foregoing is true and correct

Signed John AlexanderTitle Operations ManagerDate 8/17/92

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

APPROVED
AS AMENDED

AUG 19 1992

AREA MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD