

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED
AUG 21 1992OIL CON. DIV.
DIST. 31. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator
Dugan Production Corp.3. Address and Telephone No.
P.O. Box 420, Farmington, NM 87499 (505) 325-18214. Location of Well (Footage, Sec., T., R., M., or Survey Description)
660' FSL & 585' FWL
Unit M, Sec. 14, T28N, R1W

5. Lease Designation and Serial No.

Jic. Apache Contract 241

6. If Indian, Allottee or Tribe Name

Jicarilla Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cedar Springs #1

9. API Well No.

30-039-07318

10. Field and Pool, or Exploratory Area

Boulder Mancos

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒
- Notice of Intent
-
- ☐
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☒
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☐
- Other
-
- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug well by spotting Class B + 6% gel cement plugs as follows:

1. Spot plug across 7" casing shoe (@ 3700') and slotted liner top @ 3689' from 3750' to 3659'.
2. Spot plug inside 7" casing across Mancos top @ 3093' and Mesa Verde top @ 2905' from 3143' to 2855'.
3. Perforate 7" casing 50' below 10-3/4" casing @ 152' and place cement inside and outside to surface.

Spot plugs with 8.34 lb./gal., 40 sec./qt. vis. mud. Virgin bottom hole pressure in the Gallup was 425 psi. This weight mud will provide adequate well control.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander

Title

Operations Manager

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

AUG 19 1992

MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOC