

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ Dry Hole
2. NAME OF OPERATOR  
DUGAN PRODUCTION CORP.
3. ADDRESS OF OPERATOR  
P O Box 208, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 730' FSL - 2260' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

☒ (Amending Sundry Notice of 10-17-81)

5. LEASE  
09-000241
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla Apache
7. UNIT AGREEMENT NAME  
Boulder Mancos
8. FARM OR LEASE NAME  
Boulder Apache
9. WELL NO. ~~32514~~ # 9 Boulder (BPL #9)
10. FIELD OR WILDCAT NAME  
Boulder Mancos
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 14 T28N R1W
12. COUNTY OR PARISH 13. STATE  
Rio Arriba NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7323' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugged and abandoned this well in the following manner:

1. Spotted 20 sx plug from 2799'-2699'.
2. Spotted 20 sx cement plug (Mesa Verde) from 2183-2083.
3. Shot off csg. at 1062.
4. Spotted cement plug 1100 to 1000.
5. Spotted 70 sx cement plug at base of surface casing from 180' to surface.
6. Installed dry hole marker with 5 sx.
7. Cleaned up location.
8. Planted grass in pit area.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 11-25-81

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMOCC

Approved as to plugging of the well bore.

Liability under bond is retained until surface restoration is completed.

Instructions on Reverse Side

RECEIVED

JAN 17 1985

OIL CON. DIV.  
DIST. 3

APPROVED  
AS AMENDED

JAN 10 1985

M. MILLENBACH  
AREA MANAGER