



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Delta
Lease No. 42-1-1203
Unit 1-1-51

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Perf. and Test Job</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 91-11 is located 1140 ft. from N line and 1450 ft. from E line of sec. 21
1/4 15/4 21 21 6 1-1-51
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesa Verde Sio Arriba New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the ungrazed ground derrick floor above sea level is 6400 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

drilled on completion rig and casing tested o.k. I.L. 3675'. Run lease well log, perf. 5332-46, 5425-32, 5436-46, 5490-34, w/1 shots/ft and free CG w/47,000 gals water only. @ 9000', avg 9000', Max 9000', Final 9000', to vacuum. I.L. 52 375'. Perf. 5496-5124, 5525-42, 5546-31, 5562-46, w/2 shots/ft, set BP 575' and free CG w/47,000 gals water only. @ 10000', avg 10000', Max 10000', Final 10000', to vacuum. I.L. 57 375'. Retrieved BP and perf. 5584-62, 5590-46, 5734-54, 5846-41, 5846-42, w/2 shots/ft, set BP 5875' and free CG w/47,000 gals water only. @ 14000', avg 14500', Max 14500', Final 14000', standing 2000' in 5 minutes. I.L. 52 375'. Retrieved BP and perf. 5846-46, 5875-75, 5846-5110, 5820-74, w/2 shots/ft, set BP 5842' and free CG w/47,000 gals water only. @ 20000', avg 14000', Max 14000', Final 14000', standing 2000' in 5 minutes. I.L. 52 375'. Cemented out test and set 5670.95' of 2-1/8" @ 4.75, 4-55 tubing/casing. nipple @ 5603.15'. Release rig @ 5670.95', 5-27-56.

I understand that this plan of work must receive approval in writing by the Geological Survey before operation may be commenced.

Company Pacific Petroleum / Pacific Corp.

Address 413 1/2 E. Main,
Farmington, New Mexico

By Original signed by M.A. DuncanTitle District Engineer

