



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
079289-A
Lease No. _____
Unit **San Juan 28-7 Unit**
14-08-001-459

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	Water Frac	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 11, 19 **57**

Well No. **76(N)** is located **990** ft. from **N** line and **990** ft. from **E** line of sec. **22**

NE Sec. 22 **26N** **7W** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat & Elanco **Rio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6801** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7-6-57. T.D. 5870'. P.B.T.D. 5820'. Water frac P.C. perf int. 5660-70; 5680-90; 5712-40; 5756-64; 5778-90 w/2 SFF w/60,500 gal. water & 60,000# sand. Max. pr. 1400#, avg. tr. pr. 1000#. Inj. rate 70.5 BPM. Flush 10,300 gal. Dropped 5 sets of 20 balls each.

7-7-57. T.D. 5875'. Temp. B.P. At 5350'. Water frac C.H. perf int 5140-58; 5172-86; 5190-5200; 5250-78; 5312-22 w/2 SFF w/67,788 gal. water & 60,000# sand. Max. pr. 1700#, avg. tr. pr. 1500-1600-1550-1650#, Inj. rate 72.5 BPM. Flush 9000 gal. Dropped 7 sets of 20 balls each.

7-7-57. T.D. 5875. Temp. B.P. @ 3800. Water frac P.C. perf int. 3492-3520; 3530-50; w/2 SFF w/22,680 gal. water & 40,000# sand. B.D. 1500#, max. pr. 1500#, avg. tr. pr. 1200#. Inj. rate 69 BPM. Flush 12,600 gal.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Co.**

Address **Box 997**

Farmington, N.M.

By **Original Signed D. C. Johnson**

Title **Petroleum Engineer**