


Form 9-331a
(Feb. 1961)



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079869-A
Unit San Juan 28-7 Unit
14-08-001-459

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	X
NOTICE OF INTENTION TO ABANDON WELL.....	Water Frac	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 9, 1957

Well No. 75(2M) is located 1850 ft. from NS line and 890 ft. from EW line of sec. 15

SW Sec. 15

28N

7W

N.M.P.M.

(¼ Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Wildcat & Blanco

Rio Arriba

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 6183 ft.



DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding, lbs. cement, ing points, and all other important proposed work)

5-20-57. T.D. 5260. P.B.T.D. 5220'. Water frac P.L. perf. int. 5084-92; 5100-32; 5146-60; 5170-5200 w/2 SFF w/58,500 gal. water & 38,000# sand. Max. pr. 1200#, avg. tr. pr. 1050#. Inj. rate 68.3 BPM. Flush 8300 gal. Dropped 3 groups of 46 balls each.

5-20-57. T.D. 5260'. Temp. Bridge plug at 4690'. Water frac S.H. perf. int. 4506-22; 4530-40; 4552-80; 4630-60 w/2 SFF w/61,500 gal. water & 53,800# sand. Max. pr. 2400#, avg. tr. pr. 2250#. Inj. rate 53.2 BPM. Flush 7700 gal. Dropped 3 groups of 46 balls each.

5-20-57. T.D. 5260. Temp. B.P. at 3210'. Water frac P.C. perf. int. 2863-2920 w/2 SFF w/48,500 gal. water & 40,000# sand. Max. pr. 1350#, avg. tr. pr. 1350#. Inj. rate 74.5 BPM. Flush 6000 gal.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Co.

Address Box 997

Farmington, New Mexico

Original Signed D. C. Johnson

By _____

Title Petroleum Engineer



1950