

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____
b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☒ DEEP-EN ☐ PLUG BACK ☐ DIFF. REVR. ☐ Other MV Sidetrack

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 3249 Englewood, CO 80155

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)
At surface 990'FNL 990'FEL

At top prod. interval reported below

At total depth

14. PERMIT NO. _____ DATE ISSUED _____

5. LEASE DESIGNATION AND SERIAL NO.
SF-079289

6. IF INDIAN, ALLOTTEE OR TRIBE NAME _____

7. UNIT AGREEMENT NAME
San Juan 28-7 Unit

8. FARM OR LEASE NAME _____

9. WELL NO.
23

10. FIELD AND POOL, OR WILDCAT
Blanco Mesaverde

11. SEC. T. R. M., OR BLOCK AND SURVEY OR AREA
Sec 15 T28N R7W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
NM

15. DATE SPUDDED 4/4/55 16. DATE T.D. REACHED 2/12/86 17. DATE COMPL. (Ready to prod.) 3/30/86 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6141GL 19. ELEV. CASINGHEAD _____

20. TOTAL DEPTH, MD & TVD 5500'KB 21. PLUG, BACK T.D., MD & TVD 5404'KB 22. IF MULTIPLE COMPL., HOW MANY* _____ 23. INTERVALS DRILLED BY _____ ROTARY TOOLS _____ CABLE TOOLS _____

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*
4518'-5180'KB Mesaverde 25. WAS DIRECTIONAL SURVEY MADE yes

26. TYPE ELECTRIC AND OTHER LOGS RUN
DIL, SDL 27. WAS WELL CORED no

Casing Record (Report all strings set in well)					
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	25.4#	175'KB	12 1/4"	125sx	
7"	20 & 23#	4480'KB	8 3/4"	500sx	
4 1/2"	10.50#	5500'KB	6 1/4"	200sx, 240CF	

LINER RECORD					TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	5125'KB	

21. PREPARATION RECORD (Interval, size and number)		22. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
1 JSPF - 4518-36', 4566-78', 39'46 holes		DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
2 JSPF - 5078-80', 5103-10', 5114-16', 5112-24', 5136-38', 5164-68', 5178-80', 21'42 holes		4518-4642'KB	Acidized w/1000gals wgt'd 15% Hcl, frac w/90,342gals 10# gel & 83,160# 20/40sd.
		5078-5180'KB	Acidized w/850gal 15% wgt'd Hcl, (over)

23. PRODUCTION
DATE FIRST PRODUCTION 2/22/86 PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) flowing WELL STATUS (Producing or shut-in) shut-in

DATE OF TEST 3/30/86 HOURS TESTED 3 hrs CHOKED SIZE 3/4" PROD'N. FOR TEST PERIOD → OIL—BBL. _____ GAS—MCF. 425.5 WATER—BBL. _____ GAS-OIL RATIO _____
FLOW. TUBING PRESS. 236 CASING PRESSURE 582 CALCULATED 24-HOUR RATE → OIL—BBL. _____ GAS—MCF. 3404 WATER—BBL. _____

24. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)
to be sold

25. LIST OF ATTACHMENTS
logs to be forwarded

26. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records
SIGNED Sgt McKinn TITLE Sr. Regulatory Analyst BY DATE 4/15/86

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stems, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Cliffhouse	4504'	4642'	sand, shale & gas sand, shale, coal, gas & wtr sand, shale & gas shale & gas			
Menefee	4642'	5045'				
Point Lookout	5045'	5416'				
Mancos	5416'	TD				
			32. (cont) frac w/2000bb1 1% Kcl, 10# gel & 90,000# 20/40 sd.			