

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Lane	d Office	Bev	Mexic	D			
Loas	• No	0549	73				
Unit	San	Just	26-6	Unit			
V	14-08-001-1051						

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS. NOTICE OF INTENTION TO THE PLANS. NOTICE OF INTENTION TO THE PLANS. NOTICE OF INTENTION TO RECRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA OF REPORT OF ALL OTHER DATA (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA OF REPORT OF ALL OTHER DATA (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA OF REPORT OF ALL OTHER DATA (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA OF REPORT OF ALL OTHER DATA (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA OF REPORT OF ALL OTHER DATA (INDICATE ABOVE BY CHECK MARK HATURE OF REPORT, NOTICE, OR OTHER DATA OF REPORT OF ALL OTHER (INDICATE BY CHECK MARK HATURE OF REPORT OF REPORT OF ALL OTHER (INDICATE BY CHECK MARK HATURE OF REPORT OF ALL OTHER (INDICATE BY CHECK MARK HATURE OF REPORT O	SUNDR	Y NOTICES	AND REPO	ORTS O	N WELLS	
Subsequent report of Altering Cassing. Notice of intention to record or actorize. Notice of intention to record or actorize. Notice of intention to record or actorize. Notice of intention to pull or alter casing. Notice of intention to pull or alter casing. Notice of intention to pull or alter casing. Notice of intention to abandon well. (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data). (Indicate above by check mark nature of report, notice, or other data. (Indicate above by check mark nature of report, notice, or other data. (Indicate above by line of sec. 11 (Indicate above by line of se	NOTICE OF INTENTION TO DRILL		SUBSEQUENT	REPORT OF WATE	R SHUT-OFF	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL. NOTICE OF INTENTION TO SHOOT OR ACHIDEE. NOTICE OF INTENTION TO SHOOT OR ACHIDEE. NOTICE OF INTENTION TO SHOOT OR ACHIDEE. NOTICE OF INTENTION TO BE ALTRE CASHG NOTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONAEM. INDICATE BY CHECK MARK NATURE OF REPORT OF ABANDONAEM. INDICATE. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT. INDICATE. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT. INDICATE. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT. INDICATE. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT. INDICATE. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT. INDICATE. (INDICATE BY CHANGE.	NOTICE OF INTENTION TO CHAN	GE PLANS	SUBSEQUENT	REPORT OF SHOO	TING OR ACIDIZING	
Subsequent report of Abandonment Notice of Intention to Pull on Alter Casing. Notice of Intention to Pull of Section Subjects and the Alter Casing. Notice of Intention to Pull of Section Subjects and the Intention of Intention (Notice on Intention) The elevation of the derrick floor above sea level is 6393 ft. DETAILS OF WORK (State names of and expected depths to objective anaday show does weights, and langths of proposed casings, indicate mudding jobs, camenting points, and all other imperiant proposed work. The 16-56 Total Depth 5667. Classout 5570. Nater Tractured Note Casings, indicate mudding jobs, camenting points, and all other imperiant proposed work. The 56 Total Depth 5667. Classout 570. Nater Tractured Menefee perf. int. 5326-5340, 5386-5356 with 50,400 galloms water and 50,300 galloms. The 57 Total Depth 500. Nater Tractured Menefee perf. int. 5326-5340, 5386-5356 with 50,400 galloms water and 50,300 galloms. The 57 Total Depth 500. Nater Tractured Cliff House perf. int. 5016-502 galloms. The 58 Temp, plug depth 5060. Nater Tractured Cliff House perf. int. 5016-502 galloms. Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commonced. Company Electrology Science States Sci	NOTICE OF INTENTION TO TEST	WATER SHUT-OFF	SUBSEQUENT	REPORT OF ALTE	RING CASING	
NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARKING TO MARK NATURE OF REPORT, NOTICE, OR OTHER DATA). S. MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT, NOTICE, OR OTHER DATA NATIONAL MARK NATURE OF REPORT NATIONAL MARK	NOTICE OF INTENTION TO RE-DI	RILL OR REPAIR WELL	1 11			164
Well No. 56 is located 1090 ft. from S line and 990 ft. from W line of sec. 11 Sk Section 11 26H 6: BEFM (Nec. and Sec. No.) (Twp.) (Range) (Range) (Range) (Range) (Meridian) (State or Territory) (State or Territory) The elevation of the derrick floor above sea level is 6393 ft. DETAILS OF WORK (State names of and expected depths to objective and any wear and since wighter, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667°. Cleanout 5570°. Water fractured Point Lockout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water & 57,200 f send. BDP 1500 f, max. pr. 2100 f, avg. tr. pr. 1900 f. Ind. rate \$4.1 bbls./min. Flush 6720 gallons. 7-18-56 Temp. Flug Depth 5360°. Water fractured Memerce perf. int. 5328-5340, 3248-5358 with 50,400 gallons water and 50,300 f send. BDP 2700 f, max. pr. 3300 f, avg. tr. pr. 2250 f. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080°. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,200 gallons water & 60,000 f send. BDP 1500 f, max. pr. 2100 f, avg. tr. pr. 1800 f. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that the plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Address Parmington, New Mexico	NOTICE OF INTENTION TO SHOO	T OR ACIDIZE	1 11		DONMENT CC	40
Well No. 56 is located 1090 ft. from S line and 990 ft. from W line of sec. 11 Sk Section 11 26H 6: BEFM (Nec. and Sec. No.) (Twp.) (Range) (Range) (Range) (Range) (Meridian) (State or Territory) (State or Territory) The elevation of the derrick floor above sea level is 6393 ft. DETAILS OF WORK (State names of and expected depths to objective and any wear and since wighter, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667°. Cleanout 5570°. Water fractured Point Lockout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water & 57,200 f send. BDP 1500 f, max. pr. 2100 f, avg. tr. pr. 1900 f. Ind. rate \$4.1 bbls./min. Flush 6720 gallons. 7-18-56 Temp. Flug Depth 5360°. Water fractured Memerce perf. int. 5328-5340, 3248-5358 with 50,400 gallons water and 50,300 f send. BDP 2700 f, max. pr. 3300 f, avg. tr. pr. 2250 f. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080°. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,200 gallons water & 60,000 f send. BDP 1500 f, max. pr. 2100 f, avg. tr. pr. 1800 f. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that the plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Address Parmington, New Mexico	NOTICE OF INTENTION TO PULL	OR ALTER CASING	SUPPLEMENT	ARY WELL HISTOR	Y X Y 10	4000 TIEN
Well No. 56 is located 1090 ft. from S line and 990 ft. from W line of sec. 11 St Section 11 268 6: IBPM (1/2 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Rio Arriba Mew Mexico (Country of Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 6393 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other improvant proposed work) 7-18-56 Total Depth 5667. Cleanout 5570. Interface tured Point Lookout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water \$ 57,200 mand. BDP 1500#, max. pr. 2100#, avg. tr. pr. 1900#. Inj. rate 54.1 bbls./min. Flush 6720 gallons. 7-18-56 Temp. Flug Depth 5360. Water fractured Menefee perf. int. 5328-5340, 5348-5358 with 50,400 gallons water and 50,300# sand. BDP 2700#, max. pr. 3300#, avg. tr. pr. 2250#. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080°. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 gallons water & 60,000# sand. EDP 1500#, max. pr. 2100#, avg. tr. pr. 1800#. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Address Box 937 Farmington, New Mexico	NOTICE OF INTENTION TO ABAN	DON WELL	Water F	LECCUTE		
Well No. 56 is located 1090 ft. from S line and 990 ft. from W line of sec. 11 St Section 11 26H 6: IMPM (Kardian) Rio Arriba Rio Arriba Rio Arriba Rev Mexico (Pield) The elevation of the derick floor above sea level is 6393 ft. DETAILS OF WORK (State names of and expected depths to objective aands; show sizes, weights, and lengths of proposed easings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667'. Cleanout 5570'. Water frectured Point Lockout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water à 57,200 man. BDP 1500 max. pr. 2100 max. pr. 2100 max. pr. 2100 max. pr. 2250 max. pr. 3300 max. pr. 2250 max. pr. 3300 max. pr. 2500 gallons. 7-18-56 Temp. Plug Depth 5300'. Water fractured Menefee perf. int. 5328-5340, 5348-5356 with 50,400 gallons water and 50,300 max. pr. 2100 max. pr. 3300 max. pr. 2250 max. pr. 3300 max. pr. 2100 max. pr. 3300 max. pr. 330	(IN	DICATE ABOVE BY CHECK MA	ARK NATURE OF REPORT	r, NOTICE, OR OTH	ER DATAUL S. GEORGE FARMINGTON, July 20	, 1 96
Rio Arriba Rew Mexico (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 6393 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667°. Cleanout 5570°. Water fractured Point Lookout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water & 57,200f sand. EDP 1500f, max. pr. 2100ff, avg. tr. pr. 1900ff. Inj. rate 54.1 bbls./min. Flush 6720 galloms. 7-18-56 Temp. Flug Depth 5380°. Water fractured Menefee perf. int. 5328-5340, 5348-5358 with 50,400 galloms water and 50,300ff sand. EDP 2700ff, max. pr. 3300ff, avg. tr. pr. 2250ff. Inj. rate 45.0 bbls./min. Flush 6720 galloms. 7-18-56 Temp. plug depth 5080°. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 galloms water & 60,000ff sand. EDP 1500ff, max. pr. 2100ff, avg. tr. pr. 1800ff. Inj. rate 54.3 bbls./min. Flush 6300 galloms. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Batural Gas Company Patrolesm Prof. 1607.	Well No. 56 is le		om. $\left\{ \begin{array}{c} S \\ S \end{array} \right\}$ line and			
Rio Arriba New Mexico (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 6393 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667°. Cleanout 5570°. Water fractured Point Lookout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water & 57,200f sand. BDP 1500#, max. pr. 2100#, avg. tr. pr. 1900#. Inj. rate 54.1 bbls./min. Flush 6720 gallons. 7-18-56 Temp. Flug Depth 5360°. Water fractured Menefee perf. int. 5328-5340, 5348-5358 with 50,400 gallons water and 50,300# sand. BDP 2700#, max. pr. 3300#, avg. tr. pr. 2250#. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080°. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 gallons water & 60,000# sand. BDP 1500#, max. pr. 2100#, avg. tr. pr. 1800#. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Farmington, New Mexico		28H	6¥:			
The elevation of the derrick floor above sea level is 6393 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed easings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667°. Cleanout 5570°. water fractured Point Lookout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water & 57,200f sand. BDP 1500f, max. pr. 2100f, avg. tr. pr. 1900f. Inj. rate 54.1 bbls./min. Flush 6720 gallons. 7-18-56 Temp. Flug Depth 5380°. Water fractured Menefee perf. int. 5328-5340, 5348-5358 with 50,400 gallons water and 50,300f sand. BDP 2700f, max. pr. 3300f, avg. tr. pr. 2250f. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080°. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 gallons water & 60,000f sand. BDP 1500f, max. pr. 2100f, avg. tr. pr. 1800f. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Patroleum Deciments D		(Twp.)	, -,	•	Home Mandan	
DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667. Cleanout 5570. Water frectured Point Leokout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water & 57,200 sand. BDP 1500%, max. pr. 2100%, avg. tr. pr. 1900%. Inj. rate 54.1 bbls./win. Flush 6720 gallons. 7-18-56 Temp. Flug Depth 5360. Water fractured Menefee perf. int. 5328-5340, 5348-5358 with 50,400 gallons water and 50,300% sand. BDP 2700%, max. pr. 3300%, avg. tr. pr. 2250%. Inj. rate 45.0 bbls./win. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 gallons water & 60,000% sand. BDP 1500%, max. pr. 2100%, avg. tr. pr. 1800%. Inj. rate 54.3 bbls./win. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Address Box 997 Farmington, New Mexico		(Coun				
DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed easings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667°. Cleenout 5570°. Water frectured Point Leokout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. unter & 57,200f sand. BDP 1500f, max. pr. 2100f, avg. tr. pr. 1900f. Inj. rate 54.1 bbls./min. Flush 6720 gallons. 7-18-56 Temp. Flug Depth 5360°. Water fractured Menefee perf. int. 5328-5340, 5348-5358 with 50,400 gallons water and 50,300f sand. BDP 2700f, max. pr. 3300f, avg. tr. pr. 2250f. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080°. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 gallons water & 60,000f sand. EDP 1500f, max. pr. 2100f, avg. tr. pr. 1800f. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Address Box 997 Farmington, New Mexico By Detroleum Nacional Company Partyleum Partyleum	•	•				
DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed easings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667°. Cleenout 5570°. Water frectured Point Leokout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. unter & 57,200f sand. BDP 1500f, max. pr. 2100f, avg. tr. pr. 1900f. Inj. rate 54.1 bbls./min. Flush 6720 gallons. 7-18-56 Temp. Flug Depth 5360°. Water fractured Menefee perf. int. 5328-5340, 5348-5358 with 50,400 gallons water and 50,300f sand. BDP 2700f, max. pr. 3300f, avg. tr. pr. 2250f. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080°. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 gallons water & 60,000f sand. EDP 1500f, max. pr. 2100f, avg. tr. pr. 1800f. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Address Box 997 Farmington, New Mexico By Detroleum Nacional Company Partyleum Partyleum	The elevation of the der	rick floor above sea	level is 6393	ft.		
(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) 7-18-56 Total Depth 5667°. Cleenout 5570°. Water fractured Point Lookout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water & 57,200 gama. BDP 1500#, max. pr. 2100#, avg. tr. pr. 1900#. Inj. rate 54.1 bbls./min. Flush 6720 gallons. 7-18-56 Temp. Flug Depth 5380°. Water fractured Memerice perf. int. 5328-5340, 5348-5358 with 50,400 gallons water and 50,300# sand. BDP 2700#, max. pr. 3300#, avg. tr. pr. 2250#. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080°. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 gallons water & 60,000# sand. BDP 1500#, max. pr. 2100#, avg. tr. pr. 1800#. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company Box 997 Farmington, New Maxico Box 997 Farmington, New Maxico						
7-18-56 Total Depth 5667. Cleanout 5570. Water fractured Point Leokout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water & 57,200 sand. BDP 1500 nex. pr. 2100 nex. pr. 2300 nex. pr. 250 nex. pr. 250 nex. pr. 250 next. pr. 2						
7-18-56 Total Depth 5667. Cleenout 5570. Water fractured Point Lookout perf. int. 5446-5466, 5512-5522, 5446-5466 with 57,600 gals. water & 57,200 sand. BDP 1500#, max. pr. 2100#, avg. tr. pr. 1900#. Inj. rate 54.1 bbls./min. Flush 6720 gallons. 7-18-56 Temp. Plug Depth 5360. Water fractured Menefee perf. int. 5328-5340, 5348-5358 with 50,400 gallons water and 50,300# sand. BDP 2700#, max. pr. 3300#, avg. tr. pr. 2250#. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 gallons water & 60,000# sand. BDP 1500#, max. pr. 2100#, avg. tr. pr. 1800#. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company R1 Paso Hatural Gas Company Address Box 997 Farmington, New Maxico	(State names of and expected dep	hs to objective sands; show: ing points, and s	sizes, weights, and len all other important pro	gths of proposed oposed work)	casings; indicate mudding jo	bs, cement-
5348-5358 with 50,400 gallons water and 50,300# sand. BDP 2700#, mex. pr. 3300#, avg. tr. pr. 2250#. Inj. rate 45.0 bbls./min. Flush 6720 gallons. 7-18-56 Temp. plug depth 5080'. Water fractured Cliff House perf. int. 5016-5026 5034-5042, 5052-5068 with 58,800 gallons water & 60,000# sand. BDP 1500#, max. pr. 2100#, avg. tr. pr. 1800#. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Address Box 997 Farmington, New Maxico By Saturday Fragistary	Water frectured Po	int Leokout peri	f. int. 5446- BDP 1500#,	max. pr.	-5522, 5446-5466 2100#, avg. tr.	with pr.
5034-5042, 5052-5068 with 58,800 gallons water & 60,000# sand. HDP 1500#, max. pr. 2100#, avg. tr. pr. 1800#. Inj. rate 54.3 bbls./min. Flush 6300 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Hatural Gas Company Address Box 997 Farmington, New Maxico By Destrolasm Englisher	5348-5358 with 50,	400 gallons wate	er and 50,300	# sand. B	DP 2700#, mex. p	⊢5340, æ. 3300#,
Company R1 Paso Hatural Gas Company Address Box 997 Farmington, New Maxico By Retroleum Fragiener	5034-5042, 5052-50	68 with 58,800 a	gellons water	& 60,000#	send. EDP 1500	₩, wax.
Address Box 997 Farmington, New Mexico By Soul	I understand that this plan of	work must receive approva	al in writing by the Geo	ological Survey be	fore operations may be com	nenced.
Farmington, New Mexico By Soyl	Company K1 Paso H	atural Gas Compa	eny			
Farmington, New Mexico By Bottoner	Address Box 997				- <i>1</i>	
Title Petroleum Engipeer	•	n, New Mexico		By	25 Boyl	
			т	itle Petrol	oum Engipeer	_