NO. OF COPIES RECEIVED 3		OFTFILE	Form C-103
DISTRIBUTION		\ \rull\rull\rull\	Supersedes Old C-102 and C-103
SANTA FE /	NEW MEXICO OIL CONS		Effective 1-1-65
FILE /		OCT 1 1 1967	
U.S.G.S.		OIL CON COM.	State Fee. X
LAND OFFICE		DIST. 8	
OPERATOR /		0101. 8	5, State Oil & Gas Lease No.
			mmmmmm
SUNDRY (DO NOT USE THIS FORM FOR PROPUSE "APPLICATION")	NOTICES AND REPORTS ON OSALS TO DRILL OR TO DEEPEN OR PLUG BIN FOR PERMIT -" (FORM C-101) FOR SUC	WELLS ACK TO A DIFFERENT RESERVOIR. H PROPOSALS.)	7. Unit Agreement Name
OIL GAS WELL X	OTHER-		San Juan 28-5 Unit
2. Name of Operator			8. Form or Lease Name San Juan 28-5 Unit
El Paso Natural Gas Co	MONTO		9. Well No.
3. Address of Operator	Orthos		69
Box 990. Farmington. 1	ew Mexico - 6(401		10. Field and Pool, or Wildcat
1 -	No seek h	1550	Basin Dakota
UNIT LETTER B 119	PEET PROM THE NOTED	LINE AND	
THE Fact LINE, SECTION	33 TOWNSHIP 28N	RANGE 5W NMPM.	
	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County
	6600, CT		Rio Arribe
16. Cl. 1. A		lature of Notice, Report or Otl	her Data
NOTICE OF IN			REPORT OF:
	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
PERFORM REMEDIAL WORK	P204 AND ABARDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
TEMPORARILY ABANDON	CHANGE PLANS	CASING TEST AND CEMENT JOB	
PULL OR ALTER CASING	CHANGE PLANS	, —	ture Treatment X
OTHER		V	
17. Describe Proposed or Completed Op- work) SEE RULE 1103.	erations (Clearly state all pertinent det	ails, and give pertinent dates, including	estimated date of starting any proposed
•	l, drilled surface hole	•	
On 9-16-67 Ran 10 joints 9 5/8", 32.30#, H-40 casing (323') set at 334' w/270 sacks cement			
On 9-16-67 Ran 10 join circulated to surface.	ts 9 5/8", 32.30#, H-40 W.O.C. 12 hours, test	casing (323') set at 33 ed w/600#/30 Min. 0. K.	4 w/270 sacks cement
On 10-8-67 T. D. 7910', ran 249 joints 4 1/2", 11.6 & 10.5# J-55 casing (7900') set at			
70101 Wheet college at 7807! second stage college at 5076', third stage college at 5000'.			
Cemented first stage w/300 sacks cement, second stage w/200 sacks, third stage w/175 sacks.			
W.O.C. 18 hours.			
on 10-9-67 P.B.T.D. 78	79'. Tested casing to	4000# 0. K. Spotted 300	gal. 7 1/2% regular
acid. Ferf. Dakota 76	32-48', 7682-90', 7724-	40', 7790-98', 7822-30'	W/16 SPZ. Frac
- 160 000H Ind/60 cond	6k 260 cml water. Max	. or. 4000#。BDP 1100#。	tr. pr. 3400-3000-4000F.
I.R. 28.3 BPM. Droppe	d 4 sets of 16 balls ca	ch, flushed v/5292 gal.	water. ISIP 2007,
5 Min. 2300#, 15 Min.	2200#, 30 Min. 2000#.		
18. I hereby certify that the information	above is true and complete to the best	of my knowledge and belief.	
Original Signed F.	1. WOOD Pe	troleum Engineer	DATE 10-10-67
SIGNED CHIEFICE OF	TITLE		
		TIDUDINGOD DISC	OCT 111967
Firm. Co	lines TITLE	UPERVISOR DIST. #3	DATE
APPROVED BY			_
CONDITIONS OF APPROVAE, IF ANY	1		