Form	
(May	1963)

STATES SUBMIT IN TRIPLICATE® THE INTERIOR (Other instructions on reverse side) UNITED STATES DEPARTMENT OF

Form approved. Budget Bureau No. 42 R1424. 5. LEASE DESIGNATION AND SERIAL NO.

G. IF INDIAN, ALLOTTEE OR TRIBE NAME

12. COUNTY OR PARISH | 13. STATE

New Mexico

Rio arriba

SF 079051-B

01011					
NOTICES	ΔND	REPORTS	ON	WELL	S

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	
OIL GAS WELL X OTHER	San Juan 28-6 Unit
NAME OF OPERATOR	8. FARM OR LEASE NAME San Juan 28-6 Unit
El Paso Natural Gas Company B. ADDRESS OF OPERATOR	9. WELL NO.
PO Box 990, Farmington, NM 87401 1. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*	10. FIELD AND POOL, OR VIVE AND
See also space 17 below.) At surface 1750'S, 890'E	So. Blanco Pictured Cliffs 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	Sec. 35, T-28-N, R-6-W

16.

14. PERMIT NO.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

6352'GL

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:			
•				WATER SHUT-OFF X REPAIRING W.	ELL
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WALLE SHOT-OFF	[
FRACTURE TREAT		MULTIPLE COMPLETE		FRACIORE TABLETHEM!	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING ABANDONMEN	·
REPAIR WELL		CHANGE PLANS		(Other)	n Well
(Other)			<u>L</u>	Completion or Recompletion Report and Log form	

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *
 - TD 3226'. Ran 102 joints 2 7/8", 6.4#, J-55 production casing, 3215' set 4-30-73 at 3226'. Baffle set at 3216'. Cemented with 271 a.ft. cement. WOC 18 hours. Top of cement at 2225'.
 - PBTD 3216'. Tested casing to 4000#-OK. Perf'd 3124-40' and 3150-62' 6-15-73 with 30 shots per zone. Frac'd with 30,000# 10/20 sand and 30,366 gallons treated water. Dropped one set of 30 balls. Flushed with 777 gallons water.



SIGNED . Ducco	Drilling Clerk	June 19, 1973
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE