

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR  
EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR  
BOX 990, FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990'S, 1750'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☒  
☒  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 080505A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
SAN JUAN 28-6 Unit

8. FARM OR LEASE NAME  
SAN JUAN 28-6 UNIT

9. WELL NO.  
211

10. FIELD OR WILDCAT NAME  
BASIN DAKOTA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 8, T-28-N, R-6-W  
NMPM

12. COUNTY OR PARISH  
RIO ARriba

13. STATE  
NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6838' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3/28/78: T.D. 4039'. Ran 99 joints 7", 20#, K-55 intermediate casing, 4027' set at 4039'. Cemented with 264 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2650'.

4/3/78: T.D. 8176'. Ran 258 joints 4 1/2", 10.5#, K-55 production casing, 8166' set at 8176'. Float collar set at 8169'. Cemented with 633 cu. ft. cement. WOC 18 hours. Top of cement 3100'.

6/6/78: PBSD 8169'. Tested casing to 4000#, OK. Perfed 7946, 7952, 7958, 7964, 7979, 8057, 8062, 8067, 8091, 8106, 8119, 8125' w/1 SPZ. Fraced with 80,000# 40/60 sand and 81,500 gallons treated water. Flushed with 5300 gallons water.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. H. Bisco TITLE Drilling Clerk DATE 6/7/78

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED  
JUN 15 1978

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.