

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
BURLINGTON RESOURCES
OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
O 990' FSL 1750' FEL, Sec. 8, T-28-N, R-6-W, NMPM

5. Lease Number
SF-080505-A

6. If Indian, All. or Tribe Name

Unit Agreement Name
San Juan 28-6 Unit

8. Well Name & Number
San Juan 28-6 U#211

9. API Well No.
30-039-20842

10. Field and Pool
Basin Dakota

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☒ Notice of Intent	☐ Abandonment	☐ Change of Plans
☐ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other - tubing repair	

13. Describe Proposed or Completed Operations

It is intended to repair the tubing on the subject well according to the attached procedure.

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Altman (LTL8) ^{for} Title Regulatory Administrator Date 9/9/98
TLW

(This space for Federal or State Office use)

APPROVED BY /s/ Duane W. Spencer Title _____ Date SEP 15 1998
CONDITION OF APPROVAL, if any:

NMOC

San Juan 28-6 Unit #211
Basin Dakota
Unit O, Sec. 8, T-28-N, R-6-W
Latitude / Longitude: 36° 40.26858' / 107° 29.21538'
Recommended Tubing Repair Procedure 8/25/98

Project Justification: This well was drilled in 1978 and completed in the Dakota. The lease operator reports equalized tubing and casing pressures and suspects a hole in the tubing.

NOTE: ALL DEPTHS ARE MEASURED FROM KB. KB to GL was 10'.

1. Comply with all NMOCD, BLM and Burlington safety and environmental regulations. Prior to moving in rig, make one-call and then verify rig anchors and dig pit.
2. MIRU workover rig. NU relief line and blow well down (kill with 2% KCL water only if necessary). ND WH and NU BOP. Test and record operation of BOP rams. Replace any WH valves that do not operate properly. Test secondary seal and install or replace if necessary.
3. **Dakota, 1-1/2", 2.9#, J-55 tubing set at 8103' (250 jts).** Broach tubing and set tubing plug in nipple at **8071'**. Fill tubing with half of its volume of 2% KCL to insure the tubing plug will be held in place. Release donut, pick up additional joints of tubing and tag bottom, recording the depth. PBTD should be at +/- **8169'**. TOOH and stand back 1-1/2" tubing. Visually inspect tubing for corrosion, and replace any bad joints. Check tubing for scale and notify Operations Engineer if it is present.
4. PU and TIH with 3-7/8" bit, bit sub, and watermelon mill on 2-3/8" workstring and round trip to PBTD, cleaning out with air/mist. **NOTE: When using air/mist, mist rate must not be less than 12 bph.** Speak with Operations Engineer, and if necessary, determine the best way to remove scale from the casing and perforations. LD 2-3/8" workstring.
5. TIH with one joint of 1-1/2" tubing with expendable check, F-nipple (one joint off bottom), then 1/2 of the 1-1/2" production tubing. Run a broach on sandline to insure that the tubing is clear. TIH with remaining 1-1/2" tubing. Replace any bad joints. CO to PBTD with air/mist.
6. PU above the top Dakota perforation at **7946'** and flow the well naturally, making short trips for clean-up when necessary.
7. Land tubing at **8055'**. Obtain pitot gauge from casing and report this gauge. Broach the upper 1/2 of the production tubing. ND BOP and NU WH. Pump off expendable check. Connect to casing and circulate air to assure that expendable check has pumped off. If well will not flow on its own, make swab run to SN. RD and MOL. Return well to production.

Recommended: *J. Tom Loveland* Approved: *Bruce W. Boyer* 8-31-98
Operations Engineer 8/26/98 Drilling Superintendent

Operations Engineer: L. Tom Loveland

Office 326-9771
Pager 324-2568
Home 564-4418