

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR  
BOX 990, FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1190'S, 1480'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 079520-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
SAN JUAN 28-5 Unit

8. FARM OR LEASE NAME  
SAN JUAN 28-5 Unit

9. WELL NO.  
94

10. FIELD OR WILDCAT NAME  
BASIN DAKOTA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25, T-28-N, R-5-W  
NMPM

12. COUNTY OR PARISH  
Rio Arriba

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7009' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/13/77: T.D. 4243'. Ran 102 joints 7", 20&23#, K-55 intermediate casing, 4231' set at 4243'. Cemented with 214 cu.ft. cement. WOC 12 hours, held 1200#/30 min. Top of cement 3200'.

9/19/77: T.D. 8424'. Ran 259 joints 4 1/2", 10.5 and 11.6#, K-55 and N-80 production casing, 8411' set at 8424'. Float collar set at 8416'. Cemented with 643 cu.ft. cement. WOC 18 hours, top of cement 3750'.

11/12/77: PBTD 8416. Tested casing to 4000#, OK. Perfed 8185, 8189, 8251, 8271, 8279, 8333, 8340, 8356, 8368, 8374' w/1 SPZ. Fraced with 66,000# 40/60 sand and 68,040 gallons treated water. Flushed with 5460 gallons water.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drilling Clerk DATE 11/15/77

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

NOV 17 1977

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.