

UNITED STATES
DEPARTMENT OF THE INTERIOR
*Revised Copy GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
EL PASO NATURAL GAS COMPANY

3. ADDRESS OF OPERATOR
Box 990, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2030' N, 885' E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☒
☒
☐
☐
☐
☐
☐
☐

5. LEASE
SF 079250

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 28-5 Unit

8. FARM OR LEASE NAME
San Juan 28-5 Unit

9. WELL NO.
97

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 14, T-28-N, R-5-W
N.M.P.M.

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7283' Gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-30-77: T.D. 4584'. Ran 102 jts. 7", 20 and 23#, N-80 and K-55 intermediate casing, 4572' set at 4584'. Cemented with 227 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 4200'.

10-5-77: T.D. 8638'. Ran 254 jts. 4 1/2", 10.5 and 11.6#, N-80, K-55 and J-55 production casing, 8625' set at 8638'. Float collar set at 8629'. Cemented with 633 cu. ft. cement. WOC 18 hours. Top of cement at 3600'.

11-22-77:*PBD 8629'. Tested casing to 4000#, OK. *Perforated 8517, 8545, 8572, 8581, 8585, 8596' w/1 SPZ. Fraced with 35,000# 40/60 sand and 38,400 gallons water. Flushed with 5670 gallons water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct


SIGNED W. E. Davis TITLE Drilling Clerk DATE March 23, 1978

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



57