

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY
3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1040' FSL x 1570' FWL, Section 26,
AT SURFACE: T-28-N, R-4-W
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO: | | SUBSEQUENT REPORT OF: | |
|--------------------------|--------------------------|-----------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | | <input type="checkbox"/> |
| (other) | | Spud & Set Csg. | |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" hole on 2/4/78. Drilled to 310'. Set 8-5/8" 24# K-55 casing at 309' with 200 sx Class "B", 2% CaCl₂. Circulated 6 sx. Pressure tested to 600#; held OK.

Drilled 7-7/8" hole to a total depth of 4350'. Set 4-1/2" 10.5# K-55 casing at 4350' with 1100 sx Class "B", 50:50 Poz, 6% gel, 2 lbs. medium Tuf Plug per sx. Tailed in with 100 sx Class "B" cement. Circulated 50 bbls. good cement.

Rig released 2/13/78.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED E. E. SVOBODA

TITLE Area Adm. Supvr.

DATE 3/8/78

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

5. LEASE

NM 14920

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Valencia Canyon Unit

8. FARM OR LEASE NAME

9. WELL NO.

17

10. FIELD OR WILDCAT NAME

Choza Mesa Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SE/4 SW/4 Section 26,

T-28-N, R-4-W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM


14. API NO.

30-039-21598

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7249' GL, 7259' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



RECEIVED

MAR 13 1978

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.