

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR
BOX 289, FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1150'W, 245'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
SF 07841

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 287 Unit

8. FARM OR LEASE NAME
San Juan 287 Unit

9. WELL NO.
246

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec 8 T-28-N R 7-W NMPN

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DE KDB, AND WD)
6852' GL

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☒
☒
☐
☐
☐
☐
☐
☐
☐

DEC 11 1973

(NOTE) Report results of multiple completion or zone change on Form 9-330.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/5/78: T.D. 3836'. Ran 92 joints 7", 20# K-55 intermediate casing, 3825' set at 3836'. Cemented with 280 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2500'.

10/11/78: T.D. 8037'. Ran 222 joints 4 1/2", 10.5# K-55 production casing 8026' set at 8037'. Float collar set at 8020' Cemented with 654 cu. ft. cement. WOC 18 hours. Top of cement at 3500'.

11/27/78: PBTD 8020'. Tested casing to 4000#, OK. Perforated 7773, 7780, 7788, 7795, 7802, 7867, 7906, 7933, 7950, 7955, 7984 with 1 SPZ. Fraced w/72,000# 40/60 sand and 82,000 gal. slick water. Flushed w/5000 gal. water

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. P. Davis TITLE Drilling Clerk DATE 12/4/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

