

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other
well well
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 790'N, 1850'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☒
☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 078498A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 28-7 Unit
8. FARM OR LEASE NAME
San Juan 28-7 Unit
9. WELL NO.
252
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 32, T-28-N, R-7-W
N.M.P.M.
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6036' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
MAY 3 1979
U.S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-16-79: TD 2876'. Ran 71 jts. 7", 20#, KS intermediate casing, 2864' set at 2876'. Cemented w/264 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 1770'.

1-21-79: TD 7074'. Ran 215 jts. 4 1/2", 10.5# & 11.6#, production casing 7063' set at 7074'. Float collar set 7056'. Cemented w/654 cu. ft. cement. WOC 18 hours. Top of cement at 2500'.

4-29-79: PBTD 7056'. Tested casing to 4000#, OK. Perfed Dak. 6828, 6834, 6840, 6846, 6920, 6947, 6953, 6959, 6979, 6986, 6999, 7018, 7042' w/1 SPZ. Fraced w/79,000# 40/60 sand and 89,000 gal. treated water. Flushed w/4704 gal. water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. P. Bisco TITLE Drilling Clerk DATE April 30, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
MAY 4 1979
OIL CON. COM.
DIST. 3