

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
BLM

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1 Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2 Name of Operator

CONOCO INC.

3 Address and Telephone No

10 DESTA DR. STE. 100W, MIDLAND, TX. 79705-4500 (915) 686-5424

4 Location of Well (Footage, Sec., T. R. M. or Survey Description)

1550' FSL & 1840' FEL, SEC 16, T 28N, R 07W, UNIT LTR 'J'

5 Lease Designation and Serial No

San Juan 28-7 Unit #195M

6 If Indian, Allottee or Tribe Name

7 If Unit or CA, Agreement Designation

8 Well Name and No.

San Juan 28-7 Unit #195M

9 API Well No.

30-039-21689

10 Field and Pool, or Exploratory Area

Blanco Mesaverde/Basin Dakota

11 County or Parish, State

Rio Arriba, NM

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Repon  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☒ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other downhole commingle

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracrunng  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

Note: Repon results of multiple completion Wdl Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-31-96 MIRU. POOH w/ 1 1/2" tbg. GIH W/ 2 3/8" tbg & scraper to 7008', POOH. GIH set CIBP @ 5375'. Found top of cement @ 3170'. Perf Point Lookout W/ 3 1/2" gun, 1 shot every other foot, @ 4992-5081, 5026-30, 5052-54, 5064-66, 5074-76, 5088-90, 5136-40, 5165-67, 5177-79, 5087-89, 5196-5200, 5213, 5233, 5274-76, 5304, 5316, 5327, for a total of 39 holes. Acid W/ 1000g 15% NEFE HCL W/ 58 1.1 BS. Frac W/ 2591 bbl 10# Linear gel W/ 150,000# 20/40 Brady sand, flushed W/ slick water. Set CIBP @ 4980'. Frac Menefee W/ 3 1/8" gun, 1 shot every other foot, @ 4564-66, 4642-54, 4663-65, 4712-14, 4783-87, 4808-10, 4832-36, 4857-59, 4864-68, 4886-94, 4924-26, 4939-41, 4950-66'. AQcid W/ 1000g 15% NEFE HCL W/ 64 1.1 BS. Frac W/ 2021 bbl 10# Linear gel W/ 135,600# 20/40 Brady sand, flusher W/ 89 bbl slick water. Set CIBP @ 4550'. Perf Cliffhouse, 1 shot every other foot, @ 4376-78, 4384-88, 4412-42, 4474-76, 4484-98, 4510-20', for a total of 37 holes. Acid W/ 1000g 15% NEFE HCL W/ 55 1.1 BS. Frac W/ 2432 bbl 10# Linear gel W/ 149,900# 20/40 Brady sand, flushed W/ 74 bbl slick water. GIH W/ metal muncher nill, tag sand @ 4471' wash to 4501', circ hole clean, drill out CIBP @ 4550'. Tag sand @ 4680', C/O to CIBP @ 4980', drill out CIBP. GIH tag fill @ 5010', C/O to CIBP @ 5373', drill out CIBP, POOH. GIH to pbsd @ 7239', pooh. GIH w/ 2 3/8" tbg and install Plunger Lift system.  
7-1-96 RDMO. Return well to production as a downhole commingled Dakota / Mesaverde producer.

Test dated 7-1-96: 25 bopd, 1 BWPD, 570 MCF, 300# TP, 500# CP, Oil Gravity 54.

RECEIVED  
OCT 3 1 1996

OIL CON. DIV.  
DIST. 3

14 I hereby certify that the foregoing is true and correct

Signed Bill R. Keathly

Title Bill R. Keathly  
Sr. Regulatory Specialist

Date 10-23-96

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_  
Conditions of approval if any: \_\_\_\_\_

ACCEPTED FOR RETURN

OCT 29 1996

BLM(6), BRK, PONCA, DJS, FILE ROOM

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON DISTRICT OFFICE

\*See Instruction on Reverse Side

AMCO

10476