

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.
3. ADDRESS OF OPERATOR
BOX 990, FARMINGTON, NEW MEXICO
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2480'S, 1615'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☒
☒
☐
☐
☐
☐
☐
☐

5. LEASE
SF 079290
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
SAN JUAN 28-7 UNIT
8. FARM OR LEASE NAME
SAN JUAN 28-7 UNIT
9. WELL NO.
258
10. FIELD OR WILDCAT NAME
BASIN DAKOTA
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 23, T-28-N, R-7-W
NMPM
12. COUNTY OR PARISH
RIO ARriba
13. STATE
NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6649' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/27/78: T.D. 3622'. Ran 117 joints 7", 20#, K-55 intermediate casing, 3610' set at 3622'. Cemented with 239 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2650'.

6/2/78: T.D. 7833'. Ran 241 joints 4 1/2", 10.5 and 11.6#, K-55 casing liner 7823' set at 7833'. Float collar set at 7824'. Cemented with 654 cu. ft. cement. WOC 18 hours. Top of cement 3200'.

6/13/78: PBTD 7824'. Tested casing to 4000#, OK. Perfed 7609, 7619, 7624, 7639, 7645, 7726, 7731, 7736, 7777, 7802' w/1 SPZ. Fraced with 87,000# 20/40 sand and 78,830 gallons Gelled water. Flushed with 5100 gallons water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J. P. Buico TITLE Drilling Clerk DATE 6/14/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

JUN 20 1978

U. S. GEOLOGICAL SURVEY
LUNDS, COLO.