

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1850' FNL & 1700' FEL (Unit G)
Sec. 7, T28N, R3W, NMPMFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

JC 83

6. If Indian, Allottee or Tribe Name

Jicarilla Apache
Tribe

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Jer #2

9. API Well No.

30 039 21755

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐
- Notice of Intent
-
- ☒
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☒
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☐
- Other

- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Set cast iron bridge plug @ 3924'.
2. Spot 14 cu. ft. class "B" cement on top of bridge plug @ 3924'. Fruitland plug 3767' - 3924'.
3. Spot 14 cu. ft. class "B" cement plug @ 3702. Ojo Alamo plug 3545' - 3702'.
4. Fill 4-1/2" casing with 26 cu. ft. class "B" w/4% gel from 286' to surface.
5. Pump down bradenhead with 71 cu. ft. class "B" w/4% gel to fill surface casing - 4-1/2" annulus to 286'. Surface plug 0' - 286'.
6. Set dry hole marker.

Job complete 8/15/97.

* Procedure amended verbally by David Spitzer (BLM) to set cast iron bridge plug above Fruitland and pump surface plug down 4-1/2" x 8-5/8" annulus on 8/15/97.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander Title Vice-PresidentDate 8/18/97

(This space for Federal or State office use)

Approved by David Spitzer Title Chief, Lands and Mineral ResourcesDate SEP 16 1997

Conditions of approval, if any:

Restore surface as per attached letter (original sent w/ NOI)