UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

REPAIR WELL

| Dec. 1973 | Budget Bareau No. 42-K1424 | | | | |
|---|---|--|--|--|--|
| UNITED STATES | 5. LEASE | | | | |
| DEPARTMENT OF THE INTERIOR | SF 079250 | | | | |
| GEOLOGICAL SURVEY | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | | | | |
| SUNDRY NOTICES AND REPORTS ON WELLS | 7. UNIT AGREEMENT NAME | | | | |
| (Do not use this form for proposals to crill or to deepen or plug back to a different | San Juan 28-5 Unit | | | | |
| reservoir. Use Form 9–331–C for such proposals.) | 8. FARM OR LEASE NAME | | | | |
| 1. oil ca gas 🖼 | San Juan 28-5 Unit | | | | |
| 1. oil gas 🔀 other | 9. WELL NO. | | | | |
| 2. NAME OF OPERATOR | 102 | | | | |
| El Paso Natural Gas Company | 10. FIELD OR WILDCAT NAME | | | | |
| 3. ADDRESS OF OPERATOR | Basin Dakota | | | | |
| Box 289, Farmington, New Mexico 87401 | 11. SEC., T., R., M., OR BLK. AND SURVEY OR | | | | |
| 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) | AREA Sec. 11, T-28-N, R-5-W N.M.P.M. | | | | |
| AT SURFACE1180'S, 470'E | 12. COUNTY OR PARISH 13. STATE | | | | |
| AT TOP PROD. INTERVAL: | Rio Arriba New Mexico | | | | |
| AT TOTAL DEPTH: | 14. API NO. | | | | |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, | | | | | |
| REPORT, OR OTHER DATA | 15. ELEVATIONS (SHOW DF, KDB, AND WD) | | | | |

(NOTE: Report results of multiple completion or zone

change or Form 9-330.)

7471' G.L.

| (other) | | | | | | | | |
|---|---------------------|---------------|------------|------------------|---------------|----------------------|-----------------------------|--------------|
| 17. DESCRIBE PROPOSED including estimated dat measured and true verti | e of starting any p | roposed work. | If well is | directionally of | irillea, give | and give subsurfa | pertinent d ce locations | ates, and |

SUBSEQUENT REPORT OF:

TD 4752'. Ran 116 joints 7", 20 & 23#, N80 & K-55 intermediate casing, 4740' set at 4752'. Cemented w/274 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement 4400'.

| Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is to | | | Set @ <i>C⁽¹⁾</i> | |
|--|---------------------------------|---------------|------------------------------|--|
| 18. I hereby certify that the foregoing is to Succession | true and correct | lerkbateA | ugust 21, 1979 | |
| | (This space for Federal or Stat | e office use) | | |
| APPROVED BY | TITLE | DATE | | |

AUG 2 9 1979