

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR

EL PASO NATURAL GAS COMPANY

3. ADDRESS OF OPERATOR

Box 289 Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1520' N, 1650' W

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE

SF 080505 - A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 28-6 Unit

8. FARM OR LEASE NAME

San Juan 28-6 Unit

9. WELL NO.

57A

10. FIELD OR WILDCAT NAME

Blanco - Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 13, T-28-N, R-6-W N.M.P.M.

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6606'

'GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-1-79 PBTD 6121'. Tested casing to 3500#, OK. Perfed P.L. 5684, 5702, 5707, 5712, 5755, 5759, 5771, 5778, 5791, 5796, 5822, 5830, 5846, 5894, 5918, 5937, 5944, 5960, 5984, 6008, 6030, 6037, 6066, 6100' with 1 SPZ. Fraced with 76,500# 20/40 sand, 153,000 gal. water. Flushed with 7,640 gal. water. Perfed C.H. & Men 5180, 5198, 5264, 5276, 5286, 5291, 5296, 5307, 5312, 5331, 5336, 5352, 5358, 5398, 5420, 5440, 5482, 5504, 5509, 5538, 5561, 5583, 5609, with 1 SPZ. Fraced 76,000# 20/40 sand, 152,000 gal. water. Flushed with 7,600 gal water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Busco TITLE Drilling Clerk DATE Sept. 6, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

SEP 12 1979