

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1700' S, 1690' E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☒

☐

☐

☐

☐

☐

☐

5. LEASE

NM 02805

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 28-6 Unit

8. FARM OR LEASE NAME

San Juan 28-6 Unit

9. WELL NO.

5 A

10. FIELD OR WILDCAT NAME

Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 14, T-28-N, R-6-W

N.M.P.M.

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6410' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-24-79: PBDT 5908'. Tested casing to 3500#, OK. Perfed 5450,5460,5466,5472,5478,5484, 5489,5499,5505,5522,5536,5544,5552,5552,5569,5580,5587,5607,5621,5671,5695,5720, 5729,5786,5806,5830,5875' W/1 SPZ. Fraced w/84,500# 20/40 sand, 169,000 gal. water. Flushed w/7,200 gal. water.

8-25-79: Perfed C.H.& Men. 4964,4983,5023,5030,5040,5056,5072,5083,5089,5095,5111,5126, 5178,5186,5193,5220,5267,5329' W/1 SPZ. Fraced w/55,000# 20/40 sand, 110,000 gal. water. Flushe w/6,900 gal. water.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED

*A. B. Buco*

TITLE

Drilling Clerk

DATE

August 27, 1979


(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:



AUG 29 1979