

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR  
PO Box 289, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1460'S, 970'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: same as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- TEST WATER SHUT-OFF ☐ ☐
- FRACTURE TREAT ☐ ☐
- SHOOT OR ACIDIZE ☐ ☐
- REPAIR WELL ☐ ☐
- PULL OR ALTER CASING ☐ ☐
- MULTIPLE COMPLETE ☐ ☐
- CHANGE ZONES ☐ ☐
- ABANDON\* ☐ ☐
- (other) Plug back & sidetrack

5. LEASE  
SF 079193
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
San Juan 28-6 Unit
8. FARM OR LEASE NAME  
San Juan 28-6 Unit
9. WELL NO.  
60A
10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 21, T-28-N, R-6-W  
NMPM
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6486' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Dropped 14 drill collars and 6 joints of drill pipe in hole (Depth at this time was 4845'). Fished out four drill collars and six joints of drill pipe. Left ten drill collars, 3" bit sub and bit in hole, total length left in hole was 315'. Top of fish at 4530'. Dropped 50 sks. of Class "B" neat cement with 2% calcium chloride on top of fish. Approximate fill up was 277' in this 6 1/4" open hole. Top of plug at 4253'. Set 7" retainer at 3644' in 7" casing and squeezed with 100 sks. Class "B" neat cement with 2% calcium chloride followed by 50 sks. Class "B" neat cement with 2% calcium chloride and 10% sand.

Verbal permission to do this was obtained on April 22, 1979.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED Mike R. Rinehart TITLE Drilling Engineer DATE April 23, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: