Form 9-331 Dec. 1973

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Dec. 1973	Budget Bureau No. 42-R1424		
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE SF 079193		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 28-6 Unit 8. FARM OR LEASE NAME		
1. oil gas well other 2. NAME OF OPERATOR	San Juan 28-6 Unit 9. WELL NO. 62A		
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Blanco M.V.		
Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA Sec. 22, T-28-N, R-6-W N.M.P.M.		
AT SURFACE: 1090'S, 1490'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH Rio Arriba New Mexico 14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6581' G.L.		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

PBTD 6033'. Tested casing to 3500#, OK, Perfed P.L. 5606, 5625, 5631, 5637, 5643,5648, 5663, 5669, 5675, 5681,5686,5723,5740,5747, 5754,5783,5809,5858, 5910.5929.5936.5952.5997'. W/1 SPZ. Fraced w/80,000# 20/40 sand, 176,500 gal. water. Flushed w/7,500 gal. water. Perfed Men. & C.H. 5083, 5101, 5108,5158,5164,5180,5186,5191,5213,5217,5286,5292,5316,5333,5341,5414,5419, 5426,5440,5516,5522,5560'. W/1 SPZ. Fraced w/69,000# 20/40 sand, 138,000 gal. water. Flushed w/7,100 gal. water.

Subsurface Safety Valve: Manu. and Type			Set @	—— ———————————————————————————————————	
18. I hereby certify that the foregoing is t				No of	
SIGNED N. B. Suisco	TITLEDrilling	Clerk DATE _	August 21, 1979) ************************************	
	(This space for Federal or Sta	te office use)			
APPROVED BY	TITLE	DATE		Vi	

AUG 2 9 1979