Dec. 1973 Budget Bureau No. 42-R1424 **UNITED STATES** 3000 3000 36 (35) 36 (35) 5. LEASE 5 6 6 DEPARTMENT OF THE INTERIOR % ≴ ⋶ SF 079289 **GEOLOGICAL SURVEY** 6. IF INDIAN, ALLOTTEE OR TRIBE NAME # 2 2 5 to 7. UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS ON WELLS ö San Juan 28-7 Unit (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 8. FARM OR LEASE NAME @ 즟 San Juan 28-7 Unit WELL NO. STARES S gas well \mathbf{x} well 9. WELL NO. 🖫 3 , Les 2. NAME OF OPERATOR 10. FIELD OR WILDCAT NAME El Paso Natural Gas Company Blanco M.V. 3. ADDRESS OF OPERATOR 11. SEC., T., R., M., OR BLK. AND SURVEY OR P.O. Box 289, Farmington, New Mexico 87401 AREA Sec 12 T-28-N R-7-W 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) N.M.P.M. AT SURFACE: 1460'S, 990'E 12. COUNTY OR PARISH 13. STATE AT TOP PROD. INTERVAL: 17 july 18 jul AT TOTAL DEPTH: 14. API NO. dyot Stufft Stufft 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, 5 REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6822 ! GL 🥌 🖁 💆 គ 2800 REQUEST FOR APPROVAL TO: SUBSECUENT REPORT OF: thogen bri. otstä yna ot zeigon i e i lenol s ÷, TEST WATER SHUT-OFF FRACTURE TREAT يرا SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) MULTIPLE COMPLETE ಕರ್<u>ತ</u> thunder the body the CHANGE ZONES the state of the s ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 6-25-79: TD 3901'. Ran 96 joints 7", 20#, K-55 intermediate casing, 3890' set at 3901'. Cemented w/272 cu.ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 2450'. 6-28-79: TD 6253'. Ran 80 joints 4 1/2", 10.5#, K-55 casing liner, 2512; 3741-6253'. Float collar set at 6236'. Cemented w/438 cu.ft; cement. WOG 18 hours. oni simberduc Jould Include John Staberduc 51..12 s Haw 61 de 2010q. To fuent OIL COM: COM. Subsurface Safety Valve: Manu. and Type _ i elseo ize, in ize, in jouther 5 de 8 9 DIST. 3 18. I hereby certify that the foregoing is true and correct SIGNED A _ TITLE Drilling Clerk __ DATE July

(This space for Federal or State office use)

APPROVED BY TITLE . DATE CONDITIONS OF APPROVAL, IF ANY:

jon tement in the metal in the metal in the metal in the content of the plugs. The conditions in the condi Ť, ě

S. GEOLOGICAL SURVEY DURANGO, COLO.

See Instructions on Reverse Side