

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 910' FSL x 870' FWL Section 35,
AT TOP PROD. INTERVAL: Same T28N, R4W
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF
- ☐
-
- FRACTURE TREAT
- ☐
-
- SHOOT OR ACIDIZE
- ☐
-
- REPAIR WELL
- ☐
-
- PULL OR ALTER CASING
- ☐
-
- MULTIPLE COMPLETE
- ☐
-
- CHANGE ZONES
- ☐
-
- ABANDON*
- ☐

SUBSEQUENT REPORT OF:

- ☐
-
- ☐
-
- ☐
-
- ☐
-
- ☐
-
- ☐
-
- ☐
-
- ☐

(other) Completion Procedure

5. LEASE
NM 14923
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Valencia Canyon Unit
8. FARM OR LEASE NAME
9. WELL NO.
40
10. FIELD OR WILDCAT NAME
Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SW/4 SW/4 Section 35 T28N R4W
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
30-039-22082
15. ELEVATIONS (SHOW DF, KDB, AND WD)
7264' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 10-2-79. Displace hole with 2% KCL water and pressure tested to 3500#, held okay. Perforated first stage from 6311' to 6438' with 2 spf, total of 70 holes.

Sand water fraced with 22,000 gallons frac fluid and 38,400# of sand. Perforated second stage from 6040' to 6244' with 2 spf, total of 86 holes.

Sand water fraced second stage with 36,000 gallons frac fluid and 52,500# of sand.

Flowed well back and swabbed. Released completion rig on 10-8-79.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Dist. Adm. Supr. DATE 10/31/79

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

