HNITED STATES

	DEPARTMENT OF THE INTERIOR	5. LEASE
	DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	SF 080430 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	GEOLOGICAL SURVET	G. II INDIAN, ALLOTTEE OR TRIBE NAME
	SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
	(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form $9-331-C$ for such proposals.)	San Juan 28-6 Unit 8. FARM OR LEASE NAME
		San Juan 28-6 Unit
	well well other	9. WELL NO.
	2. NAME OF OPERATOR	28A (PM)
	El Paso Natural Gas Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Undes PC & Blanco MV
	P.O. Box 289, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 18, T-28-N, R-6-W
	below.) AT SURFACE: 1120'N, 1200'W	NMPM
	AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico
	AT TOTAL DEPTH:	14. API NO.
	16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
	REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0017 (GL
	TEST WATER SHUT-OFF	
	SHOOT OR ACIDIZE	
	REPAIR WELL	(NOTE:\ Report results of multiple completion or zone change on Form 9–336)
	MULTIPLE COMPLETE	Chaire, on Form 19-330.
	CHANGE ZONES	
	(other)	and the second of the second o
	17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	a all portions details and single and details
	including estimated date of starting any proposed wởੈਸk. If well is d measured and true vertical depths for all markers and zones pertinen	irectionally drilled, give subsurface locations and it to this work.)*
2-3-81:	: PBTD 6033'. Tested casing to 3500#, OK. Peri 5597,5601,5620,5624,5628,5673,5677,5681,5696,	
	5819,5844,5860,5930,5939,5954' W/1 SPZ. Frace	
	gal. wtr. Flushed w/ 7440 gal. wtr.	
		5230 5321 5327 5344 5351 5370 5374
	5067,5073,5079,5155,5172,5180,5212,5218,5224,5230,5321,5327,5344,5351,5370,5376,5433' W/1 SPZ. Fraced w/ 57,500# 20/40 sand, 115,000 gal. wtr. Flushed w/ 7100	
	gal. wtr.	
	Perfed Pic. Cliffs: 3416-40' W/16 SPZ. Fraced w/ 24,000# 10/20 sand, 34,000 gal. wtr. Flushed w/ 5800	
	gal. wtr.	and, 34,000 gal. wtr. Flushed w/ 5800
	8	
	Subsurface Safety Valve: Manu. and Type	Set @ Ft.
	18. I hereby certify that the foregoing is true and correct	
	SIGNED . J. Ducco TITLE Drilling Clerk DATE Feb. 17, 1981	
	(This space for Federal or State office use)	
	APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
	FEATURE IN ART.	

u._pul

TO STATE OF THE