

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P.O. Box 289, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

940'S, 790'E

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

SF 079289

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 28-7 Unit

8. FARM OR LEASE NAME

San Juan 28-7 Unit

9. WELL NO.

61A

10. FIELD OR WILDCAT NAME

S. Blanco PC Ext. & Blanco

11. SEC., T., R., M., OR BLK. AND SURVEY OR MV

AREA Sec. 10, T-28-N, R-7-W
NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.


15. ELEVATIONS (SHOW DF, KDB, AND WD)

6572' GL

RECEIVED
APR 15 1981

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

NOTES - Report results of multiple completion or zone change on Form 9-330.



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-9-81: PBSD 5927'. Tested casing to 3500#, OK. Perf'd Point Lookout: 5487, 5491, 5494, 5512, 5516, 5520, 5545, 5549, 5560, 5564, 5568, 5577, 5614, 5628, 5644, 5705, 5745, 5768, 5907, 5848, 5898' W/1 SPZ. Fraced w/ 45,000# 20/40 sand, 145,500 gal. wtr. Flushed w/6890 gal. wtr.
Perf'd Cliff House & Menefee: 4968, 5003, 5021, 5064, 5070, 5074, 5078, 5096, 5100, 5103, 5245, 5371' W/1 SPZ. Fraced w/ 27,500# 20/40 sand, 82,500 gal. wtr. Flush w/ 6890 gal. wtr.
Perf'd Pic. Cliffs: 3319-30, 3342-58, 3364-85' W/1 SPZ. Fraced w/ 48,000# 10/20 sand, 58,000 gal. wtr. Flushed w/ 5600 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. J. Mico TITLE Drilling Clerk DATE April 13, 1981

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

APR 21 1981

NMOCC

FARMINGTON DISTRICT

BY _____