5. LEASE



UNITED STATES

DEPARTMENT OF THE INTERIOR	SF 079521	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
CHAIRDY MOTIOES AND DEPORTS ON WELLS	7. UNIT AGREEMENT NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	San Juan 28-5 Unit	
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas 📉	San Juan 28-5 Unit	
1. oil gas 🕅 other	9. WELL NO.	
2. NAME OF OPERATOR	38A	
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Tap. PC Ext. & Blanco MV	
P.O. Box 289, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 32 T-28-N R-5-W	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec.32, T-28-N, R-5-W	
AT SURFACE: 845'S, 1610'E	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL:	Rio Arriba New Mexico	
AT TOTAL DEPTH:	14. API NO.	, iliani
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		There is the
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6481' GL	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	The state of the s	
TEST WATER SHUT-OFF		\
FRACTURE TREAT SHOOT OR ACIDIZE		N. Committee of the com
REPAIR WELL	(NOTE: Report results of multiple completion or zone	.,
PULL OR ALTER CASING	change on Form 9–330.)	:
MULTIPLE COMPLETE	$\mathcal{L}_{\mathrm{const}} = \sqrt{\mathcal{O}} U_{\mathrm{const}}$	
ABANDON*		
(other)		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertined 1-4-80: PBTD 5925'. Tested casing t 3500#,	irectionally drilled, give subsurface locations and nt to this work.)*	
5490,5496,5500,5505,5514,5520,5526, 5603,5610,5627,15632,5720,5736,5815' sand, 1,000 gal. wtr. Flushed w/ 8	5537,5550,5570,5578,5584,5590, W/1 SPZ. Fraced w/56,000# 20/40	
Perfed Cliff House & Menefee:		
4983,4987,5000,5013,5024,5044,5061,5066,5086,5112,5118,5124,5214,5290,5436,5441' W/1 SPZ. Fraced w/39,000#20/40 sand 112,000 gal.		
	9,000#20/40 Sand 112,000 gar.	
wtr. Flushed w/7000 gal. wtr. Perfed Pictured Cliffs:		
3296-3308,3308-3320,3332-3342,3343-	3356' W/1 SPZ. Fraced w/46,000#	Philips
10/20 sand 62,000 gal. wtr. Flushe	d w/5800 gal. wtr.	DAMES IN THE STATE OF
, ,	· ·	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.	
18. I hereby certify that the foregoing is true and correct		eri eri
	lerk DATE January 14, 1981	
(This space for Federal or State of		
APPROVED BY TITLE	DATE	** ·
CONDITIONS OF APPROVAL, IF ANY: AUGEPTED FULL RESULTS NMC		
JAN 21 1981		

*See Instructions on Reverse Side

FARMINGTON DISTRICT