ATH #

30-039-22233

Page 1 Revised 10/01/78

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator <u>B</u>	URLINGTON RESOURCE	S OIL & GAS CO.		Lease	SAN JUAN 28-	5 UNIT		Well No. 38A
Location	**	32 Twp.	0001	Rge.	005/4/	County	RIO ARRIBA	
of Well:	Unit O Sect	32 Twp. RESERVOIR OR POOL		,	PE OF PROD.	 	OD OF PROD.	PROD. MEDIUM
	NAME	and beautiful and a second	_		(Oil or Gas)	(Flo	w or Art. Lift)	(Tbg. or Csg.)
Upper Completion	PICTURED CLIFFS				Gas	Flow		Tubing
Lower Completion	MESAVERDE				Gas Flow			Casing
		PRE-F	LOW SHUT-IN	PRESS	URE DATA			
Upper	Hour, date shut-in Length of time shut-in			SI press. psig Stabili			Stabilized? (Y	es or No)
Completion	7/16/99	120 Hours		355				
Lower Completion	7/16/99	72 Hou	ırs		380			
			FLOW TES	T NO.				
Commenced	at (hour,date)*	7/19/99			Zone producing	(Upper or	Lower) LO	WER
TIME	LAPSED TIME		SURE		PROD. ZONE			
(hour,date)	SINCE*	Upper Completion	Lower Comple	oletion TEMP		REMARKS		
7/20/99	96 Hours	360	178					
7/21/99	120 Hours	365 175						
								
Production rat	e during test	<u> </u>						
Oil:	BOPD based on Bbls. in		n	Hours. G		Grav.	Grav. GOR	
Gas:	_	MCFPD; Tested thru (Orifice or Meter): 				
		MID-	TEST SHUT-IN	PRESS	SURE DATA			
Upper Completion	Hour, date shut-in	Length of time shut-in						(es or No)
Lower Completion	Hour, date shut-in	Length of time shut-	-in	SI press. psig Stabilized? ((es or No)		

(Continue on reverse side)

			ELUW TEST NO.	2					
Commenced at (hour, d	ate)**			one producing (Upper or L	ower):				
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	REMARKS				
		Upper Completion	Lower Completion	TEMP.	KLMANK				
-									
Production rate du	ring test								
Oil:	B0	OPD based on	Bbls. in	Hours	Grav	GOR			
Gas:		MCFPI	D: Tested thru (Orific	e or Meter):					
Remarks:									
	at the information he $\overline{OCT} \; 1$	o 1000	-	best of my knowledge					
17			9	Operator Burlington Resources					
	il Conservation Divi		B	V Kolory &	low				
	HNAL SIGNED BY	CHARLIE T. PERFE	-		0				
By				Title Operations Associate					
Title	PEPUTY OIL & GA	AS INSPECTOR, DIS	-	Date Friday October 08 1999					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Tes No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone w th a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pre-sures may be taken as desired, or may be requested on wells which have previously show questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of such test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual ompletion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Cffice of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).