

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other
2. NAME OF OPERATOR  
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR  
Box 289, Farmington, New Mexico
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1840'N, 1045'W  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 078497-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
San Juan 28-7 Unit
8. FARM OR LEASE NAME  
San Juan 28-7 Unit
9. WELL NO.  
30-A (PM)
10. FIELD OR WILDCAT NAME  
Blanco PC & Blanco MV
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 18, T-28-N, R-7-W  
N.M.P.M.
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6854' GL

(NOTE: Report results of multiple completion or change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-26-80: PBDT 6121'. Tested casing to 3500#, OK. Perfed P.L. 5592,5616,5629,5653, 5681,5697,5701,5711,5721,5731,5735,5747,5752,5761,5772,5815,5828,5871,5906, 5931,5987,6005,6031,6058' W/1 SPZ. Fraced w/47,000# 20/40 sand, 94,000 gal. wtr. Flushed w/ 7518 gal. wtr.

Perfed C.H. & Men. 5024,5100,5108,5121,5126,5131,5137,5146,5152,5158,5165, 5184,5196,5208,5222,5228,5234,5242,5248,5367,5405,5427,5516,5532,5546'W/1 SPZ. Fraced w/54,500# 20/40 sand, 109,000 gal. wtr. Flushed w/ 7098 gal. wtr.

Perfed PC. 3463-3469; 3472-3480; 3490-3498; 3532-3543' W/16 SPZ. Fraced w/ 35,000# 10/20 sand, 40,000 gal. wtr. Flushed w/ 5880 gal. wtr. 3 sets of 16 balls each. Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. P. Alarco TITLE Drilling Clerk DATE May 29, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NMCCG

JUN 3 1980

FARMINGTON DISTRICT