

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1960'S, 1390'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE

SF 078417

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 28-7 Unit

8. FARM OR LEASE NAME

San Juan 28-7 Unit

9. WELL NO.

256 E

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 17, T-28-N, R-7-W
NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE


New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6637' GL

(NOTE: Report results of multiple completions on one change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-14-81: Spudded well. Drilled surface hole. Ran 7 joints 9 5/8", 40#, 66-S surface casing 318' set at 332'. Cemented w/ 325 cu. ft. cement. Circ. to surface. WOC 12 hours; held 600#/30 minutes.

1-17-81: TD 3649'. Ran 84 joints of 7", 20#, K-55 intermediate casing 3637' set at 3649'. Cemented w/ 361 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement 2800'.

1-21-81: TD 7805'. Ran 193 joints of 4 1/2", 10.5#, K-55 casing 7793' set at 7805'. Float collar set at 7798'. Cemented w/ 685 cu. ft. cement. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. D. Lusco TITLE Drilling Clerk DATE January 30, 1981

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

FEB 04 1981

FARMINGTON DISTRICT

NMOCC

*See Instructions on Reverse Side