

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1000'N, 1690'W
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 080505
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 28-5 Unit
8. FARM OR LEASE NAME
San Juan 28-5 Unit
9. WELL NO.
59M
10. FIELD OR WILDCAT NAME
Blanco MV & Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 30, T-28-N, R-5-W
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6582' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 5-3-81: TD 3750'. Ran 91 joints of 9 5/8", 43#, N-80 intermediate casing 3738' set at 3750'. Cemented w/ 719 cf. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 1900'.
5-7-81: TD 6144'. Ran 60 joints of 7", 23#, N-80 casing liner 2523' set 3620-6144'. Float collar set at 6119'. Cemented w/ 653 cf. cement. WOC 18 hours.
5-11-81: TD 7890'. Ran 53 joints of 4 1/2", 11.6#, K-55 casing liner 1885' set 6005-7890'. Float collar set at 7882'. Cemented w/ 336 cf. cement. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Buice TITLE Drilling Clerk DATE May 13, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

NMOCC
*See Instructions on Reverse Side

RECEIVED FOR RECORD

MAY 18 1981

FARMINGTON, N.M.